


VIANEN MISTY UNIT

PRACTICAL EXAMPLE RIGHT SIDE VIEW



ADVANTAGES

- ✓ Reduces fire risks
- ✓ Easy to install
- √ Minimal maintenance

DESCRIPTION

The Vianen Misty Unit reduces the risk of fire caused by sparks and high temperature during the cooking process, especially from charcoal grills or wood fired equipment.

The nozzles of the Misty system release a continuous fine mist spray of water during the cooking process. This highly efficient method of filtration also changes the grease from its gaseous state to condensed grease particles in the cold water mist. The Vianen high efficiency Fecon filters and separate moisture separator remove the water mist from the airstream before it enters the exhaust ductwork. The contaminated water is collected within internal channels and runs off to the drainage system.

Available is the following configurations:

| Туре | Air volume: | Dimensions: | Water usage |
|------------|-------------|------------------|-------------|
| Misty 1000 | 1000 m3/h | 1250x825x500 mm | 3.9 L/Min |
| Misty 1400 | 1400 m3/h | 1450x1225x500 mm | 5.8 L/Min |
| Misty 2000 | 2000 m3/h | 1450x1625x500 mm | 8.7 L/Min |
| Misty 3000 | 3000 m3/h | 1450x2025x600 mm | 10.6 L/Min |

TECHNICAL INFORMATION

Exhaust pressure drop : 250 Pa

Cold water connection : 3/4" outer-thread Water drain : 1" outer-thread

Water pressure : 2 Bar

SECTION VIEW 1450 950 Duct connection By Vianen



www.vianenkvs.com Tel.: (+31) 348 - 41 63 00 info@vianenkvs.nl

