

DIMMER WITH BLUETOOTH LD220WCM



Designation	LD220WCM
Effect	0-200VA
Function	Trailing edge dimmer
E-number	13 602 42
Art. number	V-4022010WCM
Maximum current	0.87A
Maximum inrush current	34A
Voltage	220-240V
Standby-effect	<0.2W
Frequency	50/60Hz
Light control	Can be controlled with one or more toggle switches, or via Casambi
Soft start	Yes
Memories last set settings	Yes, even after power outages
Overheating protection	Yes, automatic reset after error removal
Mounting	Incorporation into device box
Operating humidity	0...80%, non conductive
Operating temperature	-20°C +40°C
Size	Ø52x19mm
Weight	31g
Cable area	1,0-2,5mm ² (AWG 12-22)
Enclosure	
- Color	White
- Material	PA6
- Flame retardant class	V-0
Area of use	230V LED lamps, electronic transformers, LED ballasts, incandescent lamps and 230V halogen lamps. Do not forget to take the reactive power into account when calculating the load.
Dimming	1% - 100%
Insulation class	IP20
Enclosure class	II



Approval

CE/S

Standard

EN60669

Besöks-/postadress:

Hilma Anderssons gata 15
421 31 Västra Frölunda

Telefon/fax:

Tel. 031-23 56 00
Fax. 031-22 60 10

E-post:

info@vadsbo.net
order@vadsbo.net

Webb/Facebook:

www.vadsbo.net
facebook.com/Vadsbo

VADSBO 