





CE

|                |                       |                    |               |
|----------------|-----------------------|--------------------|---------------|
| Power          | <b>52 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>8900 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour   | <b>CW</b>             | Beam angle         | <b>120 °</b>  |
| IK             | <b>10</b>             | Protection class   | <b>IP65</b>   |




See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

|                              |                          |
|------------------------------|--------------------------|
| Product code                 | SLI028026CW_PW           |
| Power                        | 52 W                     |
| Nominal current              | 235 mA                   |
| Voltage                      | 230 V                    |
| Energy consumption           | 52 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | I                        |
| Power supply included        | +                        |
| Power factor                 | 0.92                     |
| Useful luminous flux*        | 8900 lm (360°)           |
| Luminous flux**              | 8000 lm (360°)           |
| Light efficiency             | 171 lm/W                 |
| Luminous intensity           | 2500 cd                  |
| Colour temperature           | 6000 K                   |
| Light colour                 | CW                       |
| Beam angle                   | 120 °                    |
| RA                           | 80                       |
| Uniformity of color SDCM max | 3                        |
| Dimmable                     | No                       |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 50000 h                  |
| Housing material             | POLYCARBONATE            |
| IK                           | 10                       |
| Protection class             | IP65                     |
| Colour                       | Gray/White               |
| Dimension (axbxc)            | 1550x72x70 mm            |
| For use                      | Inside/Outside           |
| Assembly method              | On the ceiling/Suspended |
| Application                  | INT/EXT                  |
| Made in                      | PRC                      |
| Other                        | MAX 16 pcs per line ,    |



\*Applies to the LED source used. \*\*Luminaire luminous flux