



CE

| | | | |
|------------------|-----------------------|--------------------|-----------------|
| Power | 25 W | Voltage | 230 V |
| Luminous flux* | 3250 lm (360°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 36, 60 ° |
| Protection class | IP20 | | |



 User manual



 Declaration of Conformity

Technical data:

| | |
|------------------------------|---------------------|
| Product code | SLI033018NW_PW |
| Power | 25 W |
| Nominal current | 120 mA |
| Voltage | 230 V |
| Energy consumption | 25 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Manufacturer of power supply | LIFUD |
| Power factor | 0.9 |
| Useful luminous flux* | 3250 lm (360°) |
| Luminous flux** | 2650 lm (360°) |
| Light efficiency | 130 lm/W |
| Luminous intensity | 6100 cd |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 36, 60 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | SANAN |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, PLASTIC |
| Protection class | IP20 |
| Colour | Black |
| Dimension (axbxc) | 170x160x74 mm |
| For use | Inside |
| Assembly method | On 3-circuit system |
| Application | INT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux