



Power	25 W	Voltage	230 V
Luminous flux*	3200 lm (360°)	Colour temperature	3000 K
Light colour	WW	Beam angle	36, 60 °
Protection class	IP20		



 User manual





 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI033019WW_PW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	LIFUD
Power factor	0.9
Useful luminous flux*	3200 lm (360°)
Luminous flux**	2600 lm (360°)
Light efficiency	128 lm/W
Luminous intensity	6100 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	36, 60 °
RA	80
Light source included	+
Producer of LED diodes	SANAN
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	White
Dimension (axbxc)	170x160x74 mm
For use	Inside
Assembly method	On 3-circuit system
Application	INT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux