



CE

Power **12-42 W**

Voltage **230 V**


Colour temperature **4000 K**

Light colour **Neutral white**


Beam angle **36, 60 °**

Protection class **IP20**




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file



Technical data:

Product code	SLI033025NW_PW
Power	12-42 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	42 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	4500 lm (360°)
Luminous flux**	1300-3800 lm (360°)
Light efficiency	107 lm/W
Luminous intensity	8900 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	Black
Dimension (axbxc)	100x96x130 mm
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux