




Power	24/30 W	Voltage	230 V
Luminous flux*	4400 lm (360°)	Colour temperature	3000/4000/6000 K
Light colour	CCT	Beam angle	120 °
IK	08	Protection class	IP65



See more on dedicated page 




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI031040CCT_PW_SENSOR
Power	24/30 W
Nominal current	135 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	4400 lm (360°)
Luminous flux**	2400/3000 lm (360°)
Light efficiency	145 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	PC
IK	08
Protection class	IP65
Colour	White
Dimension (axbxc)	320x80 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux