



CE

Power	<b>14-27 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>4000 K</b>	Light colour	<b>Neutral white</b>
Beam angle	<b>40 °</b>	UGR	<b>&lt;19</b>
IK	<b>06</b>	Protection class	<b>IP44</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI043020NW_PW
Power	14-27 W
Nominal current	125 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	3250 lm (360°)
Luminous flux**	1300-2600 lm (360°)
Light efficiency	120 lm/W
Luminous intensity	4000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	06
Protection class	IP44
Colour	White
Dimension (axbxc)	169x95 mm
Mounting hole	140 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



\*Applies to the LED source used. \*\*Luminaire luminous flux