

PRODUCT DATASHEET

BLKH RD SEN 300 P 18W CPS WT

BULKHEAD ROUND SENSOR | Robust wall and ceiling luminaire with IP65 and IK10 protection and sensor



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- Passages, underpasses
- Public areas

Product benefits

- Multiple adjustments of sensor range, daylight detection and hold time
- Highly versatile due to selectable CCT and power steps (Multi Color / Multi Lumen) on the driver
- Flexible mounting patterns for convenient installation
- Suitable for use in public areas thanks to high IK rating
- Suitable for use in dusty and damp locations thanks to high IP rating
- Suitable for use in emergency lighting systems (DC capable)
- Separate decor element available for an aesthetic and functional product design

Product features

- High frequency sensor for daylight and motion detection
- UV-stabilized polycarbonate (PC) housing, PC-diffuser
- High luminous efficacy: > 120 lm/W for 3000 K and 4000 K
- Impact resistance: IK10
- Type of protection: IP65
- Push wire terminal for tool-free connection



- Through-wiring possible

TECHNICAL DATA

Electrical data


Nominal wattage	17.5 W / 15.5 W / 13 W / 11 W ¹⁾
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	80...70...60...50 mA
Inrush current	9.5 A
Inrush current time T _{h50}	26.8 µs
Max. number of luminaires per miniature circuit breaker B16	79
Max. number of luminaires per miniature circuit breaker C10	63
Max. number of luminaires per miniature circuit breaker C16	101
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	II
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image


Photometrical data

Luminous flux	2280 lm / 1980 lm / 1690 lm / 1390 lm ¹⁾
Luminous efficacy	128 lm/W / 127 lm/W / 130 lm/W / 126 lm/W ¹⁾
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °


¹⁾ For possible options refer to lumen/power table image




BLKH 300 P 16W 830 2000lm




BLKH 300 P 16W 840 2000lm




BLKH 300 P 11W 830 1330lm




BLKH 300 P 11W 840 1390lm




BLKH 300 P 13W 830 1610lm




BLKH 300 P 13W 840 1690lm




BLKH 300 P 15.5W 830 1880lm




BLKH 300 P 15.5W 840 1980lm




BLKH 300 P 18W 830 2160lm




BLKH 300 P 18W 840 2280lm




BLKH 300 P 16W 830 2000lm




BLKH 300 P 16W 840 2000lm




BLKH 300 P 11W 830 1330lm




BLKH 300 P 11W 840 1390lm




BLKH 300 P 13W 830 1610lm




BLKH 300 P 13W 840 1690lm




BLKH 300 P 15.5W 830 1880lm



BLKH 300 P 15.5W 840 1980lm



BLKH 300 P 18W 830 2160lm




BLKH 300 P 18W 840 2280lm

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
18 W	4000 K	2280 lm	126 lm/W
18 W	3000 K	2160 lm	120 lm/W
15.5 W	4000 K	1980 lm	127 lm/W
15.5 W	3000 K	1880 lm	121 lm/W
13 W	4000 K	1690 lm	130 lm/W
13 W	3000 K	1610 lm	122 lm/W
11 W	4000 K	1390 lm	126 lm/W
11 W	3000 K	1330 lm	120 lm/W

Dimensions & Weight

Diameter	312.00 mm
Height	73.00 mm
Product weight	940.00 g



BLKH RD/SEN/DA/EM 300 P 16W

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Outdoor
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	70000 h ¹⁾
Lifespan L80/B10 at 25 °C	55000 h ¹⁾
Lifespan L80/B50 at 25 °C	65000 h
Lifespan L90/B10 at 25 °C	40000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	370...320...270...220 mA
ECG - Output ripple current	< 5 %

Sensor

Type of sensor	Motion / Light
Sensor technology	Microwave
Sensor detection angle	150 °
Sensor controlled switching time	5 s...30 min
Detection range of motion sensor	3...8 m
Detection threshold of daylight sensor	2...50 lx

Emergency lighting

Type of Emergency Lighting (EL)	EL certified driver (0Hz / DC operation) for central battery operation included
Type of emergency operation test	None
Wattage in emergency operation mode	17.5 W
Luminous flux in emergency operation mode	2280 lm

Certificates & Standards

Standards	CE / CB / UKCA / EAC / ENEC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00029-V01.01-EN
Replaceable light source (EPREL)	Only by an expert

Additional product data

Added function	EVERLOOP / MULTI SELECT
----------------	-------------------------

Accessories Optional

Product image	Product name	EAN
	BLKH RD Eyelid 300 BK	4099854286797
	BLKH RD Eyelid 300 WT	4099854286810
	BLKH RD Eyelid 250 WT	4099854286773
	BLKH RD Eyelid 250 BK	4099854286759
	LISOEV 300R 15W 830 840 BLKH	4099854311970
	DR DS-P- 18/220-240/370 BLKH	4099854286858

EQUIPMENT / ACCESSORIES

- Additional cover rings in different designs available
- Mounting screws and dowels included
- Anti-theft screw included

Upgrade and replacement components

Components Light Source

Product image	Product name	EAN
	LISOEV 300R 15W 830 840 BLKH	4099854311970

Components Driver

Product image	Product name	EAN
	DR DS-P- 18/220-240/370 BLKH	4099854286858

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	BLKH RD GEN2
 Legal information	Informationstext 18 Abs 4 ElektroG
 Legal information	Light Source Insert G11233325
 Legal information	Legal Insert G11234785
 Legal information	Safety Insert G11234787
 Declarations of conformity	BLKH RD SEN
 Declarations of conformity UKCA	BLKH RD SEN

Photometric and lighting design files	Document name
 IES file (IES)	BLKH 300 P 18W 830 2160lm
 IES file (IES)	BLKH 300 P 18W 840 2280lm
 IES files (IES, additional)	BLKH 300 P 11W 830 1330lm
 IES files (IES, additional)	BLKH 300 P 11W 840 1390lm

Photometric and lighting design files		Document name
	IES files (IES, additional)	BLKH 300 P 13W 830 1610lm
	IES files (IES, additional)	BLKH 300 P 13W 840 1690lm
	IES files (IES, additional)	BLKH 300 P 15.5W 830 1880lm
	IES files (IES, additional)	BLKH 300 P 15.5W 840 1980lm
	LDT file (Eulumdat)	BLKH 300 P 18W 830 2160lm
	LDT file (Eulumdat)	BLKH 300 P 18W 840 2280lm
	LDT files (Eulumdat, additional)	BLKH 300 P 11W 830 1330lm
	LDT files (Eulumdat, additional)	BLKH 300 P 11W 840 1390lm
	LDT files (Eulumdat, additional)	BLKH 300 P 13W 830 1610lm
	LDT files (Eulumdat, additional)	BLKH 300 P 13W 840 1690lm
	LDT files (Eulumdat, additional)	BLKH 300 P 15.5W 830 1880lm
	LDT files (Eulumdat, additional)	BLKH 300 P 15.5W 840 1980lm
	ULD file (DIALux)	BLKH RD SEN 300 P 18W CPS WT
	ROLF file (RELUX)	BLKH RD SEN 300 P 18W CPS WT
	UGR file (UGR table)	BLKH 300 P 16W 830 2000lm
	UGR file (UGR table)	BLKH 300 P 16W 840 2000lm
	UGR file (UGR table)	BLKH 300 P 11W 830 1330lm
	UGR file (UGR table)	BLKH 300 P 11W 840 1390lm

Photometric and lighting design files		Document name
	UGR file (UGR table)	BLKH 300 P 13W 830 1610lm
	UGR file (UGR table)	BLKH 300 P 13W 840 1690lm
	UGR file (UGR table)	BLKH 300 P 15.5W 830 1880lm
	UGR file (UGR table)	BLKH 300 P 15.5W 840 1980lm
	UGR file (UGR table)	BLKH 300 P 18W 830 2160lm
	UGR file (UGR table)	BLKH 300 P 18W 840 2280lm
	Light distribution curve type cone	BLKH 300 P 16W 830 2000lm
	Light distribution curve type cone	BLKH 300 P 16W 840 2000lm
	Light distribution curve type cone	BLKH 300 P 11W 830 1330lm
	Light distribution curve type cone	BLKH 300 P 11W 840 1390lm
	Light distribution curve type cone	BLKH 300 P 13W 830 1610lm
	Light distribution curve type cone	BLKH 300 P 13W 840 1690lm
	Light distribution curve type cone	BLKH 300 P 15.5W 830 1880lm
	Light distribution curve type cone	BLKH 300 P 15.5W 840 1980lm
	Light distribution curve type cone	BLKH 300 P 18W 830 2160lm
	Light distribution curve type cone	BLKH 300 P 18W 840 2280lm
	Light distribution curve type polar	BLKH 300 P 16W 830 2000lm
	Light distribution curve type polar	BLKH 300 P 16W 840 2000lm
	Light distribution curve type polar	BLKH 300 P 11W 830 1330lm
	Light distribution curve type polar	BLKH 300 P 11W 840 1390lm
	Light distribution curve type polar	BLKH 300 P 13W 830 1610lm
	Light distribution curve type polar	BLKH 300 P 13W 840 1690lm
	Light distribution curve type polar	BLKH 300 P 15.5W 830 1880lm
	Light distribution curve type polar	BLKH 300 P 15.5W 840 1980lm
	Light distribution curve type polar	BLKH 300 P 18W 830 2160lm
	Light distribution curve type polar	BLKH 300 P 18W 840 2280lm
CAD/BIM files		Document name
	BIM Revit 3D	Bulkhead Round

CAD/BIM files		Document name
	CAD STEP 3D	BLKH G2 300
Tender texts		Document name
	Tender documents	BULKHEAD ROUND SENSOR 300 P 18W CPS WT-EN


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854286247	Folding box 1	77 mm x 317 mm x 317 mm	1074.00 g	7.74 dm ³
4099854286254	Shipping box 8	650 mm x 330 mm x 335 mm	9252.00 g	71.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

BLKH RD 250					BLKH RD SEN 250				
WAC	6,5	9	6,5	6,5	WAC	10	6,5	7	6
T (Rohr)	4000	3000	4000	3000	4000	3000	4000	3000	4000
Im	1000	1100	1000	1000	800	800	710	710	800
ImW	120	120	120	120	120	120	120	120	120



	B10	B16	G10	G16
BLKH RD 250 P 10W CPS BK	155	248	155	248
BLKH RD 250 P 10W CPS WT	63	79	63	101
BLKH RD 250 P 10W CPS BK	140	224	140	224
BLKH RD 250 P 10W CPS WT	63	79	63	101

Detection Area			Hold Time			Daylight Sensor		
1	2	3	4	5	6	7	8	9
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON	ON

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.