

U N I F I T

UNI-CAS103 manual

WCD Plug & Play, relay max. 10A.



Product

The UNI-CAS103 is a Casambi WCD with EURO plug, for non-dimmable lighting and lighting with its own dimmer. The soft start with inrush current limiter ensures trouble-free switching of the lighting and a longer LED service life. The switch on the side is a manual switch and dim option.

Please note:

- Maximum load: 10A
- Not protected against overload and short circuit
- Not suitable for low-voltage halogen or LED lamps with iron core transformers

CASAMBI App:


1. Open the app and add the module to the desired network.
 2. Control by tapping the icon in the 'Lamp' tab.
-

Technical specifications

- Mains voltage: 230VAC + 10%
- Mains frequency: 50Hz
- Ambient temperature: 0 – 35 °C
- Load: 10A (resistive), 6A (LED @50Hz), 1A (LED @60Hz).
- Water resistance: IP20
- Dimensions: 55x52x60mm.
- Standards: EN60669-2, EN55015, EN61000, EN61547, EN62493
- Directives: CE (2014/30/EU, 2014/35/EU), RoHS, REACH, EuP

Warranty

No warranty for mechanical damage or improper use. 1-year warranty from the date of purchase indicated on the purchase receipt.



U N I F I T