



MANUALS



REUSABLE



EN 1492-1



DRAGON

LIFTING STRAP WITH TILTING SYSTEM

- Reusable lifting system ideal for Timber Frame elements
- Certified for lifting and reusable according to EN 1492-1 with a safety factor of 7:1
- Hole required in the element: 45 mm | 1 3/4"



CODES AND DIMENSIONS

CODE	size		WLL						pcs
			⌀		45°		60°		
	[mm]	[in]	[kg]	[lbs]	[kg]	[lbs]	[kg]	[lbs]	
DRAGON	35 x 500	1 3/8" x 19 3/4"	850	1875	595	1310	425	935	1



OCTOPUS

LIFTING EYEBOLT AND PERCUSSION NUT

- Eyebolts can be used again
- Limited wear



LIFTING EYEBOLTS

CODE	thread	rope diameter		L		capacity		colour mark	pcs
		[mm]	[in]	[mm]	[in]	[kg]	[lbs]		
OCT45512	M12	6,0	0.236"	455	17 15/16"	500	1100	red	1
OCT45516	M16	8,0	0.315"	455	17 15/16"	1200	2645	green	1
OCT45520	M20	10,0	0.394"	455	17 15/16"	2000	4410	verde	1

PERCUSSION NUT

CODE	thread	Ø hole		H	Ø flange		colour mark	pcs	
		[mm]	[in]		[mm]	[in]			
OCTM12	M12	18	3/4"	14	9/16"	60	2 3/8"	orange	1
OCTM16	M16	22	7/8"	16	5/8"	60	2 3/8"	red	1
OCTM20	M20	24	15/16"	16	5/8"	60	2 3/8"	green	1

Percussion nut that can be used once in a single lifting cycle.



REUSABLE



DM 2006/42/CE

