

Wi-Fi+LAN Kit



Data Security



Remote Upgrade



Breakpoint Retransmission



Pre-assembled, tested

Technical Parameter

Basic Parameter

Input Voltage	5V
Power	2W
Size (Length × Width × Thickness)	96±2mm × 49±2mm × 32±2mm
Operation Temperature Range	-30 ~ 60°C
Operation humidity	0 ~ 100% RH (No condensing)
Operation altitude	<4000m
Water Protection	IP65

Ethernet interface

Port	RJ45
Cable length	0.5m
Waterproof level	IP65
Communication method	LAN&WiFi

Software parameter

Configuration	APP / WEB
Language	English
Transmission speed	UART:115200bps Ethernet:10/100M adaptive
Maximum transmission distance of a network cable	100m
Operation mode	AP / STA / AP+STA
Wireless standard	802.11 b/g/n
Frequency Range	2.412GHz-2.484GHz
Certification	CE / RCM

Features

- Wi-Fi+LAN integrated into one, for centralized deployment and management - simplified configuration & O&M
- Data encrypted to ensure data security
- Supports breakpoint retransmission - automatic disconnection of broken links, reconnection and subsequent transmission to prevent data loss
- Remote upgrade - inverter program update without going on-site
- Pre-assembled, tested and shipped - no on-site installation required, stable performance