

Growatt Smart EV Charger


THOR 11AS-S/P, THOR 22AS-S/P (Three Phase)

- Compatible with all branded EV
- Integration in existing & new-installed PV system
- Charge EV with 100% renewable energy by surplus solar power
- APP smart control & smart scheduling
- IP65 design for indoor or outdoor use



GROWATT

www.ginverter.com



P O W E R
- I N G O
T O M O -
R R O W O

Datasheet*	THOR 11AS-P (WIFI/4G)		THOR 11AS-S (WIFI/4G)		THOR 22AS-P (WIFI/4G)		THOR 22AS-S (WIFI/4G)	
Input & Output								
Input voltage	400V AC							
Input frequency	50Hz							
Output voltage	400V AC							
Max. output power	11KW				22KW			
Max. output current	16A				32A			
Charging interface type	IEC 62196-2, Type 2							
Connection	Plug		Socket		Plug		Socket	
Cable Length	5m		/		5m		/	
Protection								
Over voltage protection	Yes							
Under voltage protection	Yes							
Over load protection	Yes							
Short circuit protection	Yes							
Earth leakage protection	Yes							
Over-temp protection	Yes							
Lightning protection	Yes							
Function and Accessory								
Ethernet	Yes							
LCD	Yes							
RCD	Type A + 6mA DC fault current protection (Equivalent to type B)							
Charge activation	APP/RFID							
LED Indicator light	Yes							
Emergency stop button	Yes							
Multiple workmodes	Fast/ PV Linkage/ Off-peak/ Load balancing							
General								
Protection degree	IP65							
Environment temperature	-20°C ~ +65°C							
Relative humidity	5-95% non-condensing							
Maximum altitude	<2000m							
Cooling	Natural cooling							
Standby power consumption	<8W							
Dimension (W/H/D)	295/466/189mm							
Weight	12.5kg		10kg		12.5kg		10kg	
Wall-mounting bracket/ Ground-mounting pole	Yes/Opt							
CE (LVD&EMC, EN 61851-1, EN61851-22, EN61000-6-3, EN61000-6-1), IEC62196								

* Each model has 4G or WIFI version for flexible communication.