

MULTI VARIABLE SERIES



OUTDOOR UNITS MULTI VARIABLE SERIES

ECOLOGICAL REFRIGERANT 

FEATURES

- Energy class A++/A+
- Autorestart function
- Chassis heater
- Lightweight, compact design
- High efficiency - SEER up to 7,8

STANDARD ACCESSORIES

- Pipe adapters
- Drain plugs
- Drain water adapter



MV-E14BI2
MV-E18BI2
MV-E21BI2
MV-E24BI2
MV-E28BI2
MV-E36BI2
MV-E42BI2



TECHNICAL PARAMETERS

MODEL		MV-E14BI2	MV-E18BI2	MV-E21BI2	MV-E24BI2
Number of connectable indoor units		1-2	1-2	2-3	2-3
Capacity cooling / heating	KW	4,1 / 4,4	5,3 / 5,7	6,1 / 6,5	7,1 / 8,6
Power supply	Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-	7,2 / 4,2	6,6 / 4,0	7,8 / 4,3	7,1 / 4,3
Energy class cooling/ heating (Average)	-	A++ / A+	A++ / A+	A++ / A+	A++ / A+
Sound pressure level at 1m	dB(A)	52	54	58	58
Dimension (w × h × d) / Net weight	mm/kg	822 × 550 × 352 / 30,0	822 × 550 × 352 / 32,0	964 × 660 × 402 / 47,5	964 × 660 × 402 / 47,5
Operating temperature range (Cool/Heat)	°C	-15-43 / -22-24	-15-43 / -22-24	-15-43 / -22-24	-15-43 / -22-24

MODEL		MV-E28BI2	MV-E36BI2	MV-E42BI2	
Number of connectable indoor units		2-4	2-4	2-5	
Capacity cooling / heating	KW	8,0 / 9,5	10,6 / 12,0	12,1 / 13,0	
Power supply	Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER / SCOP	-	7,2 / 4,2	7,2 / 4,0	NA	
Energy class cooling/ heating (Average)	-	A++ / A+	A++ / A+	NA	
Sound pressure level at 1m	dB(A)	58	60	60	
Dimension (w × h × d) / Net weight	mm/kg	964 × 660 × 402 / 51,0	1020 × 826 × 427 / 72,0	1020 × 826 × 427 / 73,0	
Operating temperature range (Cool/Heat)	°C	-15-43 / -22-24	-15-43 / -22-24	-15-43 / -22-24	