



Serie 421

Plaatstaal geperste gaffel, verzinkt met plaat- en boutgatbevestiging. Zwenkwielen met een afgedichte dubbele kogeldraaikrans.

Rem blokkeert wiel en draaikrans gelijktijdig.

Wielen van wit polyamide PA6 met rollager.
Hardheid wiel ca 75° Shore D.



+ Plaatbevestiging | Rollager

| | | | | | | | | | | |
|-----|----|-----|----|-----------|-----------------|----|-----|----------------|----------------|----------------|
| 80 | 25 | 105 | -- | 104 x 80 | 80 x 60 - Ø 9 | 43 | 130 | 421.110 | 421.111 | 421.112 |
| 100 | 32 | 128 | -- | 104 x 80 | 80 x 60 - Ø 9 | 40 | 200 | 421.115 | 421.116 | 421.117 |
| 125 | 35 | 155 | -- | 104 x 80 | 80 x 60 - Ø 9 | 40 | 200 | 421.120 | 421.121 | 421.122 |
| 160 | 45 | 195 | -- | 135 x 110 | 105 x 80 - Ø 11 | 55 | 300 | 421.140 | 421.141 | 421.142 |
| 200 | 50 | 235 | -- | 135 x 110 | 105 x 80 - Ø 11 | 55 | 350 | 421.145 | 421.146 | 421.147 |

+ Boutgatbevestiging | Rollager

| | | | | | | | | | | |
|-----|----|-----|--------|----|----|----|-----|----------------|----------------|----|
| 80 | 25 | 105 | Ø 12.5 | -- | -- | 43 | 130 | 421.510 | 421.511 | -- |
| 100 | 32 | 128 | Ø 12.5 | -- | -- | 40 | 200 | 421.515 | 421.516 | -- |
| 125 | 35 | 155 | Ø 12.5 | -- | -- | 40 | 200 | 421.520 | 421.521 | -- |

Ook Leverbaar:

Polyamide wielen met glijlager.

