

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Ankertros Acryl PU Lak Blank (16-0266-000)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Paint / paint-related material for industrial / professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Anker Stuy Verven B.V.

Street : Hellingwal 1

Postal code/city : NL - 8407 EM Terwispel

Telephone : +31 513 - 46 50 00

Telefax : +31 513 - 46 50 30

Information contact : info@ankerstuy.nl

1.4 Emergency telephone number

(Office hours 08:00 - 16:30 GMT +1). Outside office hours: call a Poison Center or doctor/physician.

Bundesinstitut für Risikobewertung: +49 30-18412-3460

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

Hazard classes and hazard categories

Skin Irrit. 3 · Skin Sens. 2

Physical hazards

Flammable gases : No

Flammable aerosol : No

Flammable Liquids : No

Health hazards

Acute toxicity (oral) : No

ATE - oral 11111 mg/kg

Percentage of ingredients of unknown toxicity (oral) : 0 %

Acute toxicity (dermal) : No

ATE - dermal 24444 mg/kg

Percentage of ingredients of unknown toxicity (dermal) : 0 %

Acute toxicity (inhalation) : No

ATE - inhalative (vapour) 244,4 mg/l

Percentage of ingredients of unknown toxicity (inhalation) : 0 %

Percentage of ingredients of unknown toxicity : 0 %

Skin Corrosion / Irritation : Category 3

Serious eye damage / eye irritation : No

Specific target organ toxicity (single exposure) : No

Specific target organ toxicity (Respiratory tract irritation) : No

Specific target organ toxicity (Narcosis) : No

Aspiration hazard : No

Sensitisation (Respiratory) : No

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Sensitisation (Skin) : Category 2
Germ cell mutagenicity : No
Carcinogenicity : No
Reproductive toxicity : No
Reproductive toxicity, Effects on or via lactation : No
Specific target organ toxicity (Repeated exposure) : No

Environmental hazards

Acute aquatic toxicity : No
Percentage of ingredients of unknown hazards to the aquatic environment (acute) : 0 %
Chronic aquatic toxicity : No
Percentage of ingredients of unknown hazards to the aquatic environment (chronic) : 0 %
Percentage of ingredients of unknown hazards to the aquatic environment : 0 %
Skin Irrit. 3 · Skin Sens. 2

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Special rules for supplemental label elements for certain mixtures

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE ; A MIXTURE OF: 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

BUTYL CELLOSOLVE ; REACH registration No. : 01-2119475108-36 ; EC No. : 203-905-0; CAS No. : 111-76-2
Weight fraction : $\geq 2,5 - < 10$ %
Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H312 Acute Tox. 4 ; H332 Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

2-(2-BUTOXYETHOXY)ETHANOL ; REACH registration No. : 01-2119475104-44 ; EC No. : 203-961-6; CAS No. : 112-34-5
Weight fraction : $< 2,5$ %
Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

After ingestion

When in doubt or if symptoms are observed, get medical advice. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol resistant foam; Carbon dioxide (CO₂) Extinguishing powder; Water mist;

Unsuitable extinguishing media

Strong water jet;

5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Do not allow run-off from fire-fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not inhale the vapour. Provide for sufficient ventilation.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Do not breathe gas/vapour/aerosol. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. See chapter 8 of the safety data sheet (Personal protection equipment). Never use pressure to empty container. Keep/Store only in original container. Comply with the health and safety at work laws. Do not allow to enter ground-water, surface water or drains, even not in small quantities.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Storage class (TRGS 510) : 12

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Further information on storage conditions

Use only in well-ventilated areas. Store between +5 and +35 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Store between +5 and +35 °C in a dry, well ventilated place away from sources of heat and direct sunlight. When using do not smoke. Only allow access to authorised staff. Prevent leaks and prevent soil / water pollution caused by leaks.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection



PBM-code: B

8.1 Control parameters

Occupational exposure limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 20 ppm / 98 mg/m³
Peak limitation : 4(II)
Remark : H,Y
Version : 01-09-2012

Limit value type (country of origin) : STEL (EC)
Limit value : 50 ppm / 246 mg/m³
Remark : H
Version : 08-06-2000

Limit value type (country of origin) : TWA (EC)
Limit value : 20 ppm / 98 mg/m³
Remark : H
Version : 08-06-2000

2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5

Limit value type (country of origin) : TRGS 900 (D)
Limit value : 10 ppm / 67 mg/m³
Peak limitation : 1,5(I)
Remark : Y
Version : 01-09-2012

Limit value type (country of origin) : STEL (EC)
Limit value : 15 ppm / 101,2 mg/m³
Version : 07-02-2006

Limit value type (country of origin) : TWA (EC)
Limit value : 10 ppm / 67,5 mg/m³
Version : 07-02-2006

Biological limit values

BUTYL CELLOSOLVE ; CAS No. : 111-76-2

Limit value type (country of origin) : TRGS 903 (D)
Parameter : Butoxy acetic acid / Urine (U) / At long term exposure: after several previous shifts
Limit value : 100 mg/l
Version : 31-03-2004

8.2 Exposure controls

Appropriate engineering controls

Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment

Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Eye/face protection

Suitable eye protection

Use tightly fitting safety glasses.

Skin protection

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

Hand protection

Wear suitable gloves tested to EN374. Breakthrough time (maximum wearing time).

Suitable gloves type : Disposable gloves.

Suitable material : NR (natural rubber, natural latex).

Required properties : liquid-tight.

Breakthrough time (maximum wearing time) : > 60 min

Thickness of the glove material : > 0,5 mm

Recommended glove articles : DIN EN 374

Body protection

Suitable protective clothing : Overall

Recommended material : Natural fibres (e.g. cotton)

Respiratory protection

Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

Consumer exposure controls

Measures related to consumer uses of the substance (as such or in preparations)

Do not allow to enter ground-water, surface water or drains, even not in small quantities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : viscous

Safety relevant basis data

Physical state :		liquid
Freezing point :	(1013 hPa)	No data available
Initial boiling point and boiling range :	(1013 hPa)	100 °C
Decomposition temperature :	(1013 hPa)	No data available
Flash point :		No data available
Ignition temperature :		No data available
Lower explosion limit :		No data available
Upper explosion limit :		No data available
Vapour pressure :	(50 °C)	No data available
Vapour pressure :	(20 °C)	23 hPa
Relative density :	(20 °C)	1,01 - 1,06 (Water = 1)
Water solubility :	(20 °C)	insoluble
Fat solubility :	(20 °C)	No data available.
pH :		No data available
log P O/W :		No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Cinematic viscosity :	(40 °C)	No data available
Odour threshold :		No data available
Relative vapour density :	(20 °C)	No data available
Evaporation rate :		No data available
Colour :		colourless
Odour :		characteristic
Solid content :	approx.	35 mass-%
Density :	(20 °C)	1,01 - 1,06 g/cm ³
Flow time :	(20 °C)	120 s
Viscosity :	(20 °C)	No data available
Oxidising liquids :	No data available.	
Explosive properties :	No data available.	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions(See section 7).

10.3 Possibility of hazardous reactions

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter :	LD0 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route :	Oral
Species :	Guinea pig
Effective dose :	500 mg/kg bw
Parameter :	LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route :	Oral
Species :	Guinea pig
Effective dose :	1414 mg/kg bw
Method :	OECD 401
Parameter :	LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route :	Oral
Species :	Mouse
Effective dose :	2410 - 5530 mg/kg bw

Acute dermal toxicity

Parameter :	LD0 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
-------------	---

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Exposure route : Dermal
Species : Guinea pig
Effective dose : 2000 mg/kg bw
Parameter : LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rat
Effective dose : 2000 mg/kg bw
Method : OECD 402
Parameter : LD50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 435 - 2000 mg/kg bw
Parameter : LD50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2764 mg/kg bw

Acute inhalation toxicity

Parameter : LC0 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Dog
Effective dose : 400 ppm
Exposure time : 7 h
Parameter : LC0 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Guinea pig
Effective dose : 400 ppm
Exposure time : 7 h
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalative (vapour)
Species : Rat
Effective dose : 800 ppm
Exposure time : 8 h
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 900 ppm
Exposure time : 7 h
Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 450 - 900 ppm
Exposure time : 4 h

Repeated dose toxicity (subacute, subchronic, chronic)

Subacute oral toxicity

Parameter : NOAEL(C) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Oral
Species : Rat
Effective dose : 250 mg/kg bw/day

Subacute dermal toxicity

Parameter : NOAEL(C) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 150 mg/kg bw/day
Parameter : NOAEL(C) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Exposure route : Dermal
Species : Rat
Effective dose : 200 - 2000 mg/kg bw/day

Subacute inhalation toxicity

Parameter : NOAEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Rat
Effective dose : 31 - 62,5 ppm
Parameter : NOAEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Exposure route : Inhalation
Species : Mouse
Effective dose : 31 - 62,5 ppm
Parameter : NOAEL(C) (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Exposure route : Inhalation
Species : Rat
Effective dose : 14 ppm

SECTION 12: Ecological information

Avoid release to the environment. Refer to special instructions / safety data sheet.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 1,474 g/l
Exposure time : 4 days
Parameter : LC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 1,3 g/l
Exposure time : 4 days

Chronic (long-term) fish toxicity

Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 100 mg/l
Exposure time : 21 days

Acute (short-term) daphnia toxicity

Parameter : EC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 1,55 - 1,8 g/l
Exposure time : 48 h
Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 100 mg/l
Exposure time : 48 h
Parameter : NOEC (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 100 mg/l
Exposure time : 48 h

Chronic (long-term) daphnia toxicity

Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 100 mg/l
Exposure time : 21 days
Parameter : EC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 297 mg/l
Exposure time : 21 days
Parameter : EC10 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 134 mg/l
Exposure time : 21 days

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertrios Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Acute (short-term) algae toxicity

Parameter : EC50 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 911 - 1840 mg/l
Exposure time : 72 h
Parameter : EC10 (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 308 - 679 mg/l
Exposure time : 72 h
Parameter : NOEC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 88 - 286 mg/l
Exposure time : 72 h
Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 100 mg/l
Exposure time : 4 days
Parameter : EC50 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 1,101 g/l
Exposure time : 72 h
Parameter : NOEC (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 100 mg/l
Exposure time : 4 days

Bacteria toxicity

Parameter : EC10 (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 1995 g/l
Exposure time : 30 min

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 90,4 %
Exposure time : 28 days
Method : OECD 301B
Parameter : Biodegradation (2-(2-BUTOXYETHOXY)ETHANOL ; CAS No. : 112-34-5)
Effective dose : 89 %
Exposure time : 28 days
Method : OECD 301C

12.3 Bioaccumulative potential

Parameter : Bioconcentration factor (BCF) (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Concentration : 3,2

12.4 Mobility in soil

Adsorption/Desorption

Parameter : Log KOC (BUTYL CELLOSOLVE ; CAS No. : 111-76-2)
Effective dose : 67

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive and is NOT classified as dangerous for the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

Avoid release to the environment. Refer to special instructions / safety data sheet. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

EU limit value for this product (cat. A/i): 140 g/l VOC.

Other regulations (EU)

Information according to 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

VOC-value : 60 g/l

National regulations

Technische Anleitung Luft (TA-Luft)

Weight fraction (Number 5.2.5. I) : < 5 %

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to AwSV

Percentage of carcinogenic substances WGK 3 : - 0 %

Percentage of carcinogenic substances WGK 2 : - 0 %

Percentage of carcinogenic substances : - 0 %

Percentage of substances WGK 3 : - 0 %

Percentage of substances WGK 3 with M-Factor : - 0 %

Percentage of substances WGK 3 (nwg) : + 0,0014 %

Percentage of substances WGK 2 : - 0 %

Percentage of substances WGK 2 with M-Factor : - 0 %

Percentage of substances WGK 1 : + 5,5 %

Percentage of substances non-hazardous to water (nwg) : 94,4586 %

Percentage of substances unidentified : - 0 %

Percentage of substances unidentified (nwg) : - 0 %

Percentage of floating liquids : 0 %

15.2 Chemical safety assessment

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

SECTION 16: Other information

16.1 Indication of changes

07. Hints on joint storage - Storage class · 08. DNEL/DMEL · 08. PNEC

16.2 Abbreviations and acronyms

a.i. = Active ingredient
ACGIH = American Conference of Governmental Industrial Hygienists (US)
ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
AFFF = Aqueous Film Forming Foam
AISE = International Association for Soaps, Detergents and Maintenance Products (joint project of AISE and CEFIC)
AOAC = AOAC International (formerly Association of Official Analytical Chemists)
aq. = Aqueous
ASTM = American Society of Testing and Materials (US)
atm = Atmosphere(s)
B.V. = Beperkt Vennootschap (Limited)
BCF = Bioconcentration Factor
bp = Boiling point at stated pressure
bw = Body weight
ca = (Circa) about
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
CEFIC = European Chemical Industry Council (established 1972)
CIPAC = Collaborative International Pesticides Analytical Council
CLP = REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.
Conc = Concentration
cP = CentiPoise
cSt = Centistokes
d = Day(s)
DIN = Deutsches Institut für Normung e.V.
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC = European Community; European Commission
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances (EU, outdated, now replaced by EC Number)
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EU = European Union
EWC = European Waste Catalogue
FAO = Food and Agriculture Organization (United Nations)
GIFAP = Groupement International des Associations Nationales de Fabricants de Produits Agrochimiques (now CropLife International)
h = Hour(s)
hPa = HectoPascal (unit of pressure)
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG Code = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
ISO = International Organization for Standardization
IUCLID = International Uniform Chemical Information Database
IUPAC = International Union of Pure and Applied Chemistry
kg = Kilogram
Kow = Distribution coefficient between n-octanol and water
kPa = KiloPascal (unit of pressure)
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
mg = Milligram
min = Minute(s)
ml = Milliliter
mmHg = Pressure equivalent to 1 mm of mercury (133.3 Pa)
mp = Melting point
MRL = Maximum Residue Limit
MSDS = Material Safety Data Sheet
n.o.s. = Not Otherwise Specified
NIOSH = National Institute for Occupational Safety and Health (US)
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
NOx = Oxides of Nitrogen
OECD = Organization for Economic Cooperation and Development
OEL = Occupational Exposure Limits
Pa = Pascal (unit of pressure)
PBT = Persistent, Bioaccumulative or Toxic
pH = -log₁₀ hydrogen ion concentration
pKa = -log₁₀ acid dissociation constant
PNEC = Previsible Non Effect Concentration
POPs = Persistent Organic Pollutants
ppb = Parts per billion
PPE = Personal Protection Equipment
ppm = Parts per million
ppt = Parts per trillion
PVC = Polyvinyl Chloride
QSAR = Quantitative Structure-Activity Relationship
REACH = Registration, Evaluation and Authorization of Chemicals (EU, see NCP)
SI = International System of Units
STEL = Short-Term Exposure Limit
tech. = Technical grade
TSCA = Toxic Substances Control Act (US)
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative
WHO = World Health Organization = OMS
y = Year(s)

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

16.6 Training advice

None

16.7 Additional information

None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Ankertros Acryl PU Lak Blank
Revision date : 09.04.2019
Print date : 09-04-2019

Version (Revision) : 1.2.0 (1.1.0)

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
