



Data sheet - 19-0257 Ankolux Woodfiller

Description

Ankolux Woodfiller 19-0257 is a waterborne acrylic high-quality wood filler. It is ideal for filling small longitudinal cracks as well as repairing minor damage or filling nail holes in beads. It can also be used for levelling out small uneven areas and filling pores in some timber substrates. It is fast drying and easy to apply and it also sands well. It should be used on repairs of no more than 2mm. It is suitable for both indoor and outdoor use and can be overcoated with a wide range of coatings, including the Anker Stuy Ankolux and Hydrolux ranges.

Substrate and Preparation

Suitable for all commonly used timber species. Timber moisture content should be between 12 and 16%. On Accoya this range should be 4-8%. The substrate must be clean, dry and free from dust, dirt, grease, silicone and wax. Refer to the appropriate Anker Stuy application sheet for other system products such as primers, topcoats and end grain sealers.

Application

Conditions – Do not apply at less than 5°C (air and substrate temperature) and above 80% relative humidity.

Equipment – Use a spatula or filling knife.

Procedure – Remove from the tub with the equipment described above and ensure the tub is kept closed as it will dry out if left exposed. Only remove small quantities at a time to ensure you have sufficient time to work with the filler and level off before it is dry. Work into cracks and small defects and leave slightly proud of the surface being filled. The material that stands proud of the surface can be sanded off once dry.

Drying – approximately 30 minutes at a thickness of up to 2mm. This is for a temperature of 20-23°C and a relative humidity of 50-60%. Higher humidity and lower temperature may slow drying. Drying times are affected by the amount of product applied. It is important to ensure drying is complete before overcoating. Overcoat after 1-2 hours. If in any doubt refer to the Anker Stuy Technical Department for details.

Storage and shelf life

For the best extension of shelf life store in a cool and dry environment. Ensure product is kept frost free. We recommend all stored products are used within 1 year of purchase. Anker Stuy can take no responsibility for storage issues.

Safety information - For more information, see the safety data sheet of this product.

Issue Code: 19-0257 041220

Date: 4th December 2020

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently, Anker Stuy Coatings doesn't guarantee the functionality or result and takes no responsibility in this respect. We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises. Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.

