



ANKER STUY **EXTERIOR** SOLUTIONS

Anker Stuy Coatings Ltd
Units 25 & 26 Alpha Park
Mallard way/Bretton
Peterborough
PE3 8AF
01733 215444



OPAQUE FACTORY APPLIED COATINGS EXTERIOR TIMBER WINDOWS AND DOORS:

PRIMERS



17-0535-110 \ Hydrolux Primer/Midcoat White

Spray applied quick drying primer based on special Tri-cryl technology. Komo-certified with a very low water uptake and outstanding wet adhesion. Suitable for a wide range of timbers including Accoya, Sapele, Red Grandis and European Redwood.



17-0540 \ Hydrolux Filling Primer

Spray applied specially formulated quick drying primer that fills the grain to achieve a uniform smooth surface that also hides laminations and finger joint connections on engineered timber. Can be applied on a wide range of wood species. Contains special Tri-cryl technology to provide exceptional wet adhesion and low water uptake.



17-0548 \ Hydrolux Flow-coat Primer SPC

This primer has been designed for application to single piece components. When modified to a lower viscosity of around 14 seconds Din cup 4, this primer is ideal for flow-coat application.

TOPCOAT



17-0645-110 \ Hydrolux Topcoat SM

Spray applied waterborne topcoat based on Tri-Cryl technology. The Hydrolux Topcoat has a very good coverage and superb flow. It has a short drying time, after 3 hours you can do further treatment. It is highly durable and KOMO-certified by the SKH wood institute. As well as the semi matt it is also available in semi gloss (17-0646) and gloss (17-0647) versions.

OPAQUE SITE BRUSH APPLIED COATINGS EXTERIOR TIMBER WINDOWS AND DOORS:

PRIMER



15-0170 \ Ankolux Brushing Primer

A waterborne brush applied primer with excellent adhesion and very good early water resistance. Based on alkyd emulsion technology for extra durability. Also suitable for priming interior timber surfaces.

TOPCOATS



11-0140 \ Hydrotop

Waterborne intermediate and finishing coat based on Tri-cryl technology for brush application onto suitably primed windows and doors. Also suitable as a maintenance coat on existing Hydrolux factory applied finishes.



11-0050 \ Ankolux Brilliant

Waterborne high-gloss finish for brush application onto suitably primed windows and doors. Very durable and based on alkyd-emulsion technology.

TRANSLUCENT FACTORY APPLIED COATINGS EXTERIOR TIMBER WINDOWS AND DOORS:



16-0200 \ Ankolux Basestain

Water-borne base stain available in a wide range of translucent shades. Can be applied by dipping, flow coating, and other saturation methods. Ideal as a base for the Ankolux Translucent Topcoats.



17-0658 \ Ankolux Translucent Topcoat SM

Waterborne translucent semi-matt, midcoat and topcoat. Highly translucent finish that accentuates the natural grain of the timber. Quick drying and very durable. Based on alkyd-emulsion technology and KOMO certified by the SKH wood institute. Also available as a semi-gloss finish.



17-0678 \ Ankolux Aqua Iso Primer

Isolating primer specially designed for translucent systems on oak to reduce problems with tannin staining on clear or highly translucent finishes.



17-0695 \ Ankolux Woodcoat

Waterborne translucent and opaque coating for semi-stable items such as cladding, log cabins and summer houses. Provides a highly breathable and flexible system to cope with the natural movement in the above items. Also suitable for maintaining existing windows and door finishes.



16-0219 \ Ankolux Woodstain

Waterborne translucent and opaque medium build coating for dimensionally non-stable items such as garden furniture, pergolas and fencing. Also suitable for semi-stable items such as cladding. Provides a highly breathable and flexible system to cope with the natural movement in the above items.



25-0350-000 \ Ankolux End Grain Sealer Clear

A waterborne clear primer sealer for end grain. Suitable for sealing exposed cut ends on windows and doors and plywood materials.

ANCILLARY PRODUCTS

EXTERIOR TIMBER WINDOWS AND DOORS:



20-0288 \ Ankolux Wood Repair

2 component repair set to repair rotten wood or large damages on timber items such as windows and doors.



19-0257 \ Ankolux Woodfiller

Fine surface filler to repair small damages up to 2mm deep.



19-0293 \ Ankloux V-Joint Sealer

A waterborne acrylic sealant specifically designed for forming an elastic moisture resistant join on the v-groove at corner sections on windows and doors.



998-17099 / Anker Stuy Maintenance Box

Maintenance set for timber windows and doors containing a surface cleaner to prepare the surface and a care wax to restore sheen and provide a sacrificial moisture resistant layer. To be used yearly to maintain the coated surface especially on more weathered areas.



23-0380 \ AW Glycol cleaner 5 litres

An alcohol based cleaner suitable for washing waterborne coatings off of equipment. Highly suitable for washing through spray pumps when diluted with water.



25-0352 \ Hydrolux End Grain sealer

A waterborne opaque primer sealer for end grain. Suitable for sealing exposed cut ends on windows and doors and plywood materials.

All our products are also online available at:

www.ankerstuyshop.co.uk