



# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Issue date: 11-02-2022 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : ANKOLUX SUPERHECHTPRIMER WIT  
Product code : 12-0068-110  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use

Title	Use descriptors
ANKOLUX SUPERHECHTPRIMER WIT	PC9a, PROC7, PROC10

Full text of use descriptors: see section 16

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Anker Stuy Verven B.V.

Hellingwal , 1

NL- 8407 EM Terwispe

Netherlands

T +31(0)513-465000

[info@ankerstuy.nl](mailto:info@ankerstuy.nl) - [www.ankerstuy.nl](http://www.ankerstuy.nl)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Carcinogenicity Not classified

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
EUH031 - Contact with acids liberates toxic gas.  
EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2H-isothiazol-3-one (3:1)(55965-84-9). May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ] substance with national workplace exposure limit(s) (ES, FR, PL) (Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379-17	10 – 25	Carc. 2, H351
talca ( $\text{Mg}_3\text{H}_2(\text{SiO}_3)_4$ ) substance with national workplace exposure limit(s) (ES, NL, PL)	CAS-No.: 14807-96-6 EC-No.: 238-877-9	10 – 25	Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332
butylglycol substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 111-76-2 EC-No.: 203-905-0 EC Index-No.: 603-014-00-0 REACH-no: 01-2119475108-36	1 – 2,5	Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	< 0,1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	( 0,0015 $\leq$ C $\leq$ 100) Skin Sens. 1A, H317 ( 0,06 $\leq$ C < 0,6) Skin Irrit. 2, H315 ( 0,06 $\leq$ C < 0,6) Eye Irrit. 2, H319 ( 0,6 $\leq$ C $\leq$ 100) Eye Dam. 1, H318 ( 0,6 $\leq$ C $\leq$ 100) Skin Corr. 1C, H314

Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : ATTENTION: The accumulation of dry overspray, contaminated rags, etc. may result in spontaneous combustion. Good housekeeping standards plus the regular and safe removal of waste materials will minimise the risk.  
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
<b>France - Occupational Exposure Limits</b>	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m <sup>3</sup>
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Poland - Occupational Exposure Limits</b>	
Local name	Ditlenek tytanu
NDS (OEL TWA)	10 mg/m <sup>3</sup> frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikażąca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednoczesne oznaczenie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Spain - Occupational Exposure Limits</b>	
Local name	Dióxido de titanio
VLA-ED (OEL TWA) [1]	10 mg/m <sup>3</sup>
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (14807-96-6)</b>	
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Talk
TGG-8u (OEL TWA)	0,25 mg/m <sup>3</sup> (respirabel)
Regulatory reference	Arbeidsomstandighedenregeling 2022
<b>Poland - Occupational Exposure Limits</b>	
Local name	Talk
NDS (OEL TWA)	4 mg/m <sup>3</sup> frakcja wdychalna 1 mg/m <sup>3</sup> frakcja respirabilna
Remark	Frakcja wdychalna – frakcja aerozolu wnikażąca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Frakcja respirabilna – frakcja aerozolu wnikażąca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w obszarze wymiany gazowej. Obowiązuje jednoczesne oznaczenie stężeń włókien respirabilnych azbestu.
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Spain - Occupational Exposure Limits</b>	
Local name	Talco (con fibras de amianto)
VLA-ED (OEL TWA) [1]	0,1 fibers/cm <sup>3</sup>
Remark	p (Sin embargo, no debe exceder de 2mg/m3 de partículas respirables).

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (14807-96-6)</b>	
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>butylglycol (111-76-2)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	2-Butoxyethanol
IOEL TWA	98 mg/m <sup>3</sup>
IOEL TWA [ppm]	20 ppm
IOEL STEL	246 mg/m <sup>3</sup> 246 mg/m <sup>3</sup>
IOEL STEL [ppm]	50 ppm 50 ppm
Remark	Skin Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC COMMISSION DIRECTIVE 2000/39/EC
<b>France - Occupational Exposure Limits</b>	
Local name	2-Butoxyéthanol (Butylglycol)
VME (OEL TWA)	49 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	10 ppm
VLE (OEL C/STEL)	246 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	50 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	49 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	10 ppm
Peak exposure limitation factor	2(l)
Remark	EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Germany - Biological limit values (TRGS 903)</b>	
Local name	2-Butoxyethanol
Biological limit value	150 mg/g creatinine Parameter: Butoxyessigsäure (nach Hydrolyse) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2016 DFG
Regulatory reference	TRGS 903
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	2-Butoxyethanol
TGG-8u (OEL TWA)	100 mg/m <sup>3</sup>

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>butylglycol (111-76-2)</b>	
TGG-15min (OEL STEL)	246 mg/m <sup>3</sup>
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2022
<b>Poland - Occupational Exposure Limits</b>	
Local name	2-Butoksyetanol (butoksyetylowy alkohol)
NDS (OEL TWA)	98 mg/m <sup>3</sup>
NDSCh (OEL STEL)	200 mg/m <sup>3</sup>
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Spain - Occupational Exposure Limits</b>	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
VLA-ED (OEL TWA) [1]	98 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	20 ppm
VLA-EC (OEL STEL)	245 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	50 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), VLB® (Agente químico que tiene Valor Límite Biológico).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>Spain - Biological limit values</b>	
Local name	2-Butoxietanol (Butil cellosolve; Éter monobutílico del etilenglicol)
BLV	200 mg/g creatinine Parámetro: Ácido butoxiacético - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: Con hidrólisis
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
<b>DNEL/DMEL (Workers)</b>	
Long-term - local effects, inhalation	10 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	700 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,184 mg/l

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
PNEC aqua (marine water)	0,0184 mg/l
PNEC aqua (intermittent, freshwater)	0,193 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	1000 mg/kg dwt
PNEC sediment (marine water)	100 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	100 mg/kg dwt
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l
<b>talco (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (14807-96-6)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	2,16 mg/m <sup>3</sup>
Acute - local effects, inhalation	3,6 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	43,2 mg/kg bodyweight/day
Long-term - local effects, dermal	4,54 mg/cm <sup>2</sup>
Long-term - systemic effects, inhalation	2,16 mg/m <sup>3</sup>
Long-term - local effects, inhalation	3,6 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	1,08 mg/m <sup>3</sup>
Acute - systemic effects, oral	160 mg/kg bodyweight
Acute - local effects, inhalation	1,8 mg/m <sup>3</sup>
Long-term - systemic effects, oral	160 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,08 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	21,6 mg/kg bodyweight/day
Long-term - local effects, dermal	2,27 mg/cm <sup>2</sup>
Long-term - local effects, inhalation	1,8 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	597,97 mg/l
PNEC aqua (marine water)	141,26 mg/l
PNEC aqua (intermittent, freshwater)	597,97 mg/l
PNEC aqua (intermittent, marine water)	141,26 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	31,33 mg/kg dwt
PNEC sediment (marine water)	3,13 mg/kg dwt
<b>butylglycol (111-76-2)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - systemic effects, inhalation	1091 mg/m <sup>3</sup>
Acute - local effects, inhalation	246 mg/m <sup>3</sup>

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>butylglycol (111-76-2)</b>	
Long-term - systemic effects, inhalation	98 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, inhalation	426 mg/m <sup>3</sup>
Acute - systemic effects, oral	26,7 mg/kg bodyweight/day
Acute - local effects, inhalation	147 mg/m <sup>3</sup>
Long-term - systemic effects, oral	6,3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	59 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	8,8 mg/l
PNEC aqua (marine water)	0,88 mg/l
PNEC aqua (intermittent, freshwater)	26,4 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	34,6 mg/kg dwt
PNEC sediment (marine water)	3,46 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	2,33 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	0,02 g/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	463 mg/l
<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	0,04 mg/m <sup>3</sup>
Long-term - local effects, inhalation	0,02 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - systemic effects, oral	0,11 mg/kg bodyweight/day
Acute - local effects, inhalation	0,04 mg/m <sup>3</sup>
Long-term - systemic effects, oral	0,09 mg/kg bodyweight/day
Long-term - local effects, inhalation	0,02 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	3,39 µg/l
PNEC aqua (marine water)	3,39 µg/l
PNEC aqua (intermittent, freshwater)	3,39 µg/l
PNEC aqua (intermittent, marine water)	3,39 µg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0,027 mg/kg dwt
PNEC sediment (marine water)	0,027 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,01 mg/kg dwt



# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

### PNEC (STP)

PNEC sewage treatment plant	0,23 mg/l
-----------------------------	-----------

#### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: white and white-derived colors.
Odour	: No data available
Odour threshold	: No data available
pH	: 7,5 – 8
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 60 °C
Auto-ignition temperature	: No data available

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: 23 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: 1,29 – 1,34
Density	: 1,29 – 1,34 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 800 – 1000 mPa.s
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available

### 9.2. Other information

VOC content : 19 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Contact with acids liberates toxic gas.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Acids.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	3,43 mg/l/4h

#### talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>) (14807-96-6)

LD50 oral rat	5000 mg/kg
LD50 dermal rat	2000 mg/kg
LC50 Inhalation - Rat	2100 mg/m <sup>3</sup>

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>butylglycol (111-76-2)</b>	
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rat	> 2000 mg/kg Source: ECHA

<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
LD50 oral rat	64 – 561 mg/kg
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	200 mg/kg Source: US EPA
LC50 Inhalation - Rat	171 – 2360 mg/m <sup>3</sup>
LC50 Inhalation - Rat (Dust/Mist)	0,33 mg/l Source: US EPA

Skin corrosion/irritation	: Not classified pH: 7,5 – 8
Serious eye damage/irritation	: Not classified pH: 7,5 – 8
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.

<b>butylglycol (111-76-2)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

<b>butylglycol (111-76-2)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:

<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
LOAEL (dermal, rat/rabbit, 90 days)	0,525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Aspiration hazard	: Not classified
-------------------	------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)</b>	
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>talc (Mg3H2(SiO3)4) (14807-96-6)</b>	
LC50 - Fish [1]	89,581 g/l
EC50 - Crustacea [1]	36,812 g/l
<b>butylglycol (111-76-2)</b>	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Source: ECHA
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 100 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
LC50 - Fish [1]	0,19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0,28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0,16 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	6,3 – 27,3 µg/l
NOEC (chronic)	0,1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0,098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>butylglycol (111-76-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	0,81 Source: ECHA

### 12.4. Mobility in soil

<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
Mobility in soil	12,08 Source: EPISUITE

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Not applicable

##### Transport by sea

Not applicable

##### Air transport

Not applicable

##### Inland waterway transport

Not applicable

##### Rail transport

Not applicable

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 19 g/l

### DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for ANKOLUX SUPERHECHTPRIMER WIT (cat. A/i): 140 g/l.

ANKOLUX SUPERHECHTPRIMER WIT Contains max 19,00 g/l VOC.

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

### Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

ABM category : A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen –

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### Switzerland

Storage class (LK) : LK 10/12 - Liquids

CH - VOC (SR 814.018) : 1,4104840374 %

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and acronyms:	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development, OECD
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4

# ANKOLUX SUPERHECHTPRIMER WIT

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH031	Contact with acids liberates toxic gas.
EUH208	Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A

Full text of use descriptors	
PC9a	Coatings and paints, thinners, paint removers
PROC10	Roller application or brushing
PROC7	Industrial spraying

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Carc. Not classified		Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.