



HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 22-04-2021 Revision date: 17-08-2022 Supersedes version of: 22-04-2021 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : HYDROTOP SM WHITE
UFI : 13RH-V0CS-S00W-1UPN
Product code : 11-0141-110
Type of product : Paint
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Consumer use, Professional use, Industrial use

Title	Use descriptors
HYDROTOP SM WHITE	PC9a, PROC10

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Anker Stuy Verven B.V.

Hellingwal , 1

NL- 8407 EM Terwispe

Netherlands

T +31 (0) 513 - 465 000

info@ankerstuy.nl - www.ankerstuy.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1

H317

Carcinogenicity Not classified

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction.

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P321 - Specific treatment (see supplemental first aid instruction on this label).

EUH-statements

: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Extra phrases

: The bottom under and around the object to be treated must be covered with plastic while applying this product.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
(2-methoxymethylethoxy)propanol (34590-94-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] substance with national workplace exposure limit(s) (ES, FR, PL) (Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	10 – 25	Carc. 2, H351
propane-1,2-diol substance with national workplace exposure limit(s) (PL)	CAS-No.: 57-55-6 EC-No.: 200-338-0 REACH-no: 01-2119456809-23	2,5 – 5	Not classified

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	Conc.	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS-No.: 1065336-91-5 EC-No.: 915-687-0 REACH-no: 01-2119491304-40	1 – 2,5	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 1, H410 (M=0)
(2-methoxymethylethoxy)propanol substance with national workplace exposure limit(s) (DE, ES, FR, NL, PL); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 0,1	Not classified
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	CAS-No.: 55406-53-6 EC-No.: 259-627-5 EC Index-No.: 616-212-00-7 REACH-no: 01-2120762115-60	< 0,1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Oral), H302 STOT RE 1, H372 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0,1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
kaolin substance with national workplace exposure limit(s) (PL)	CAS-No.: 1332-58-7 EC-No.: 310-194-1	< 0,1	Not classified

Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	(0,05 ≤C ≤ 100) Skin Sens. 1, H317

Note 10 : The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : PBM-code: B.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
France - Occupational Exposure Limits	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Poland - Occupational Exposure Limits	
Local name	Ditlenek tytanu
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednocześnie oznaczanie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	Dióxido de titanio
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
propane-1,2-diol (57-55-6)	
Poland - Occupational Exposure Limits	
Local name	Propano-1,2-diol
NDS (OEL TWA)	100 mg/m ³ pary i frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
(2-methoxymethylethoxy)propanol (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308 mg/m ³
IOEL TWA [ppm]	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France - Occupational Exposure Limits	
Local name	(2-Méthoxyméthyléthoxy)-propanol
VME (OEL TWA)	308 mg/m ³
VME (OEL TWA) [ppm]	50 ppm
Remark	Valeurs règlementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	310 mg/m ³
AGW (OEL TWA) [2]	50 ppm

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(2-methoxymethylethoxy)propanol (34590-94-8)	
Peak exposure limitation factor	1(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Netherlands - Occupational Exposure Limits	
Local name	Dipropyleenglycolmethylether
TGG-8u (OEL TWA)	300 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	(2-Metoksymetyloetoksy)propanol - mieszanina izomerów: 1-(2-metoksy-1-metyloetoksy)propan-2-ol, 1-(2-metoksy-2-metyloetoksy)propan-2-ol, 2-(2-metoksy-1-metyloetoksy)propan-1-ol
NDS (OEL TWA)	240 mg/m ³
NDSch (OEL STEL)	480 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Spain - Occupational Exposure Limits	
Local name	Éter metílico de dipropilenglicol
VLA-ED (OEL TWA) [1]	308 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
kaolin (1332-58-7)	
Poland - Occupational Exposure Limits	
Local name	Kaolin
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Obowiązuje jednocześnie oznaczanie stężeń frakcji respirabilnej krzemionki krystalicznej.
Regulatory reference	Dz. U. 2018 poz. 1286

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	10 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	700 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,184 mg/l
PNEC aqua (marine water)	0,0184 mg/l
PNEC aqua (intermittent, freshwater)	0,193 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1000 mg/kg dwt
PNEC sediment (marine water)	100 mg/kg dwt
PNEC (Soil)	
PNEC soil	100 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l
propane-1,2-diol (57-55-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	168 mg/m ³
Long-term - local effects, inhalation	10 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	50 mg/m ³
Long-term - local effects, inhalation	10 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	260 mg/l
PNEC aqua (marine water)	26 mg/l
PNEC aqua (intermittent, freshwater)	183 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	572 mg/kg dwt
PNEC sediment (marine water)	57,2 mg/kg dwt
PNEC (Soil)	
PNEC soil	50 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	20000 mg/l
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	2,5 mg/kg bodyweight/day
Acute - systemic effects, inhalation	2,35 mg/m ³

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Acute - local effects, inhalation	2,35 mg/m ³
Long-term - systemic effects, dermal	0,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,68 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	1,25 mg/kg bodyweight/day
Acute - systemic effects, inhalation	0,58 mg/m ³
Acute - systemic effects, oral	1,25 mg/kg bodyweight/day
Acute - local effects, inhalation	0,58 mg/m ³
Long-term - systemic effects, oral	0,05 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,17 mg/m ³
Long-term - systemic effects, dermal	0,25 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,0022 mg/l
PNEC aqua (marine water)	0,00022 mg/l
PNEC aqua (intermittent, freshwater)	0,009 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,05 mg/kg dwt
PNEC sediment (marine water)	0,11 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,21 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1 mg/l
(2-methoxymethylethoxy)propanol (34590-94-8)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	283 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	308 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	37,2 mg/m ³
Long-term - systemic effects, dermal	121 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	19 mg/l
PNEC aqua (marine water)	1,9 mg/l
PNEC aqua (intermittent, freshwater)	190 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	70,2 mg/kg dwt
PNEC sediment (marine water)	7,02 mg/kg dwt

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(2-methoxymethylethoxy)propanol (34590-94-8)	
PNEC (Soil)	
PNEC soil	2,74 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	4168 mg/l
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	0,07 mg/m ³
Acute - local effects, inhalation	1,16 mg/m ³
Long-term - systemic effects, dermal	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,023 mg/m ³
Long-term - local effects, inhalation	1,16 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,0005 mg/l
PNEC aqua (marine water)	0,000046 mg/l
PNEC aqua (intermittent, freshwater)	0,00053 mg/l
PNEC aqua (intermittent, marine water)	0,00053 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,017 mg/kg dwt
PNEC sediment (marine water)	0,0016 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,005 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	0,44 mg/l
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,966 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6,81 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1,2 mg/m ³
Long-term - systemic effects, dermal	0,345 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	4,03 µg/l
PNEC aqua (marine water)	0,403 µg/l
PNEC aqua (intermittent, freshwater)	1,1 µg/l
PNEC aqua (intermittent, marine water)	110 ng/l
PNEC (Sediment)	
PNEC sediment (freshwater)	49,9 µg/kg dw
PNEC sediment (marine water)	4,99 µg/kg dw

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

PNEC (Soil)

PNEC soil	3 mg/kg dwt
-----------	-------------

PNEC (STP)

PNEC sewage treatment plant	1,03 mg/l
-----------------------------	-----------

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective goggles. Gloves.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Liquid.
Odour	: weak. characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 60 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 8,5 – 9
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 23 hPa
Vapour pressure at 50 °C	: Not available
Density	: 1,144 g/cm ³
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 121 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	3,43 mg/l/4h

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane-1,2-diol (57-55-6)	
LD50 oral rat	22000 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit
LC50 Inhalation - Rat	> 44,9 mg/l air Animal: rat, Guideline: other:, Remarks on results: other:
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LD50 oral rat	3230 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), 95% CL: 2615 - 4247
LD50 dermal rat	> 3170 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
(2-methoxymethylethoxy)propanol (34590-94-8)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
LD50 oral rat	1056 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Remarks on results: not determinable due to absence of adverse toxic effects
LC50 Inhalation - Rat	670 mg/m ³
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LD50 oral rat	490 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified pH: 8,5 – 9
Serious eye damage/irritation	: Not classified pH: 8,5 – 9
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
NOAEL (animal/female, F1)	56,6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
propane-1,2-diol (57-55-6)	
NOAEL (subchronic, oral, animal/male, 90 days)	443 mg/kg bodyweight Animal: cat, Animal sex: male
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

(2-methoxymethylethoxy)propanol (34590-94-8)	
LOAEL (dermal, rat/rabbit, 90 days)	Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
LOAEL (dermal, rat/rabbit, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days), Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0,0067 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	20 mg/kg bodyweight Animal: rat, Guideline: other:, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (dermal, rat/rabbit, 90 days)	200 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days), Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,00116 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs (larynx) through prolonged or repeated exposure (inhalation).
Aspiration hazard	: Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
propane-1,2-diol (57-55-6)	
LC50 - Fish [1]	51600 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	51400 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	24200 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	19300 mg/l Test organisms (species): Skeletonema costatum

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane-1,2-diol (57-55-6)	
EC50 96h - Algae [1]	19000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	19100 mg/l Test organisms (species): Skeletonema costatum
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
LC50 - Fish [1]	0,9 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	1,68 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	0,42 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
(2-methoxymethylethoxy)propanol (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Poecilia reticulata
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0,5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0,5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
EC50 96h - Algae [1]	1,978 mg/l Source: Ecological Structure Activity Relationships
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)	
LC50 - Fish [1]	≈ 16,7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	2,15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2,94 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2,9 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	110 µg/l
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
propane-1,2-diol (57-55-6)	
Partition coefficient n-octanol/water (Log Pow)	0,085 Source: ECHA
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Partition coefficient n-octanol/water (Log Pow)	2,37 – 2,77
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)	
Partition coefficient n-octanol/water (Log Pow)	2,4 Source: Corporate Solution From Thomson Micromedex

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

Partition coefficient n-octanol/water (Log Pow)	0,64
Partition coefficient n-octanol/water (Log Kow)	0,7 @ 20 °C

12.4. Mobility in soil

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate (55406-53-6)

Mobility in soil	269,15
------------------	--------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 08 00 00 - WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content : 121 g/l

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products:

EU limit value for HYDROTOP SM WHITE (cat. A/d): 130 g/l.

HYDROTOP SM WHITE Contains max 121,00 g/l VOC.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Netherlands

ABM category	: A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: kaolin is listed
SZW-lijst van mutagene stoffen	: kaolin is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK)	: LK 10/12 - Liquids
CH - VOC (SR 814.018)	: 10,5961229 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development, OECD

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

HYDROTOP SM WHITE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of use descriptors

PC9a	Coatings and paints, thinners, paint removers
PROC10	Roller application or brushing

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Sens. 1	H317	Calculation method
Carc. Not classified		Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.