

**HYDROTOP (Gloss 39/semi-gloss 40/semi-matt 41) | 11-0139/40/41****PRODUCT DESCRIPTION**

Water-borne intermediate and finishing coat based on TriCryl ®. Technology for brush application onto exterior or interior timber surfaces especially suited for windows and doors.

**TECHNICAL DATA**

<b>Viscosity</b>	approx. ca. 8 Pa·s	at 20°C
<b>Density</b>	approx. 1,16 (white)	kg/l
<b>Flashpoint</b>	Not flammable	Method: Closed Cup
<b>Solid content</b>	38	% by volume
<b>Theoretical spreading rate</b>	10-15	m <sup>2</sup> /litre
<b>Storage stability</b>	12 months at	5°C - 35°C

**APPLICATION METHOD** Brush, roller, spray (cup) for horizontal

**PRODUCT PREPERATION** Ready for use - stir well before use

Best results are achieved if finished on a finely sanded surface and applied generously. When applying to previously applied paint coats, we recommend cleaning and degreasing them thoroughly and then sanding them.

<b>RECOMMENDED NO. OF COATS:</b>	2
<b>REQUIRED FILM THICKNESS:</b>	70-100µm
<b>MAXIMUM FILM THICKNESS:</b>	150µm

**SUBSTRATE PREPERATION:**

Suitable for all commonly used timber species. Timber moisture content should be between 12 and 16%. The substrate must be clean, dry and free from dust, dirt, grease, silicone and wax. Follow the appropriate Anker Stuy coating specification for other system products such as top coats and end grain sealers.

**OTHER INFORMATION:**

<b>Cleaning</b>	Clean tools and equipment with warm water
<b>Thinning</b>	As required
<b>Storage</b>	Store in a cool environment and ensure its free from frost.
<b>Shelf Life</b>	1 year if stored correctly
<b>Safety Info</b>	Please see Safety Data Sheet
<b>VOC content</b>	121g/l

Version 12072023

**MAIN PROPERTIES**

Quick drying  
Ease of use  
Brushable  
Low VOC  
outdoor/indoor

**MINIMUM RECOMMENDED SETTINGS****Air Assisted Airless (AAA)****Minimum pump size 15:1**

Fluid Pressure:	n/a
Air Assistance:	n/a
Tip Size (Thou.):	n/a
Filter size	n/a

**Airless**

Fluid Pressure:	n/a
Tip Size (Thou.):	n/a

**Conventional**

Fluid Pressure:	Compliant
Tip Size (mm):	2.5mm

**DRYING TIMES**

Drying at : 20°C and relative humidity of 65%

<b>Dust free</b>	:	60 minutes
<b>Handle</b>	:	60 minutes
<b>Sanding</b>	:	90 minutes
<b>Overcoat</b>	:	3 hours
<b>Stack</b>	:	3 hours

This product is suitable for use with Hydrolux system as an on-site touch up product, or maintenance product to recoat existing painted windows and extend lifespan.

\* Drying requires good air movement and removal of humid air from confined spaces.