

PRODUCT DATA SHEET

Rubber Studded Mat

Anti-slip, sound- and vibration-dampening rubber matting

NR/SBR

MATERIAL

65 Shore A ± 5

HARDNESS

-30° to 70°C

TEMPERATURE RANGE

3mm

THICKNESS

Rubber matting with a raised stud pattern, providing anti-slip grip, wear resistance, and sound- and vibration-dampening performance for demanding surfaces. Not resistant to oil, grease, or hydrocarbons.

Key Benefits

- ✓ Extra grip in wet or dirty conditions
- ✓ Highly wear-resistant
- ✓ Dampens contact noise and vibration
- ✓ Easy to cut to size

Applications

- Van and vehicle loading areas
- Stairs and entrances
- Shop floors
- Workshops and industrial environments



TECHNICAL SPECIFICATIONS

Reference	R-02-120-3
Rubber type	NR/SBR
Colour	Black (grey available, 1200mm width only)
Thickness	3mm
Hardness	65 Shore A ± 5
Density	1.5 g/cm ³
Tensile strength	5 MPa
Elongation at break	250%
Min. temperature	-30°C
Max. temperature	70°C
Self-adhesive	No

MATERIAL OPTIONS

Available widths (mm)*	1,200, 1,400, 1,500 (grey only available in 1,200mm)
Max. roll dimensions (mm)	1,500 × 10,000

*Looking for a different width or size? Contact us at info@geluidsisolatiedeal.nl

DISCLAIMER

The published technical data is based on research data and serves as guidance for the various applications. Due to the wide diversity of products and possible applications, the buyer must test whether the intended material meets the stated requirements. All information is subject to typographical errors, mistakes and market developments, and no rights can be derived from it.