

**Safety data sheet
according to UK REACH**

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Beast Wheel cleaner**Article number:**

04331000, 04333000, 04335000

UFI: CCV6-W0YU-R000-MQNK**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS07

Signal word Warning**Hazard statements**

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing spray.

P280 Wear protective gloves/eye protection.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 1)

P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: aqueous tenside solution with additives

Dangerous components:

CAS: 367-51-1 EINECS: 206-696-4 Reg.nr.: 01-2119968564-24-xxxx	sodium mercaptoacetate solution (46%) ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317; Aquatic Chronic 3, H412	3-<5%
CAS: 68891-38-3 NLP: 500-234-8 Reg.nr.: 01-2119488639-16-xxxx	alcohols, C12-14, ethoxylated, sulfates, sodium salts ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Aquatic Chronic 3, H412 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 5 % ≤ C < 10 %	1-<3%
CAS: 6153-56-6 EINECS: 205-634-3 Reg.nr.: 01-2119534576-33-xxxx	oxalic acid ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	1-<3%
CAS: 5949-29-1 EINECS: 201-069-1 Reg.nr.: 01-2119457026-42-xxxx	citric acid ⚠ Eye Irrit. 2, H319; STOT SE 3, H335	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

anionic surfactants	<5%
perfumes (LINALOOL)	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

After swallowing:

Rinse out mouth and then drink plenty of water.

Induce vomiting only, if affected person is fully conscious.

Call a doctor immediately.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed
sensitization
Allergic reactions
Eye irritation

4.3 Indication of any immediate medical attention and special treatment needed
Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Avoid contact with the eyes and skin.

For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 4)

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELEs		
CAS: 367-51-1 sodium mercaptoacetate solution (46%)		
Dermal	DNEL	2.06 mg/kg (worker long-term systemic effects)
Inhalative	DNEL	1.41 mg/kg (worker long-term systemic effects)
CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts		
Oral	DNEL	15 mg/kg (consumer/long-term)
Dermal	DNEL	1,650 mg/kg (consumer/long-term) 2,750 mg/kg (worker long-term)
Inhalative	DNEL	52 mg/m ³ (consumer/long-term) 175 mg/m ³ (worker long-term)
CAS: 6153-56-6 oxalic acid		
Oral	DNEL	1.14 mg/kg (consumer) (longterm systematic effects)
Dermal	DNEL	1.14 mg/kg bw/day (consumer) (longterm systematic effects) 2.29 mg/kg bw/day (worker) (longterm systematic effects)
	DNEL	0.35 mg/cm ² (consumer)
Inhalative	DNEL	4.03 mg/m ³ (worker) (longterm systematic effects)
PNECs		
CAS: 367-51-1 sodium mercaptoacetate solution (46%)		
PNEC	0.038 mg/l (freshwater (Süßwasser)) 0.0038 mg/l (water (sea water))	
CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts		
PNEC	10,000 mg/l (sewage plant) 0.24 mg/l (water (fresh water)) 0.024 mg/l (water (sea water))	
PNEC	7.5 mg/kg (gro) 0.9168 mg/kg (sediment (fresh water)) 0.09168 mg/kg (sediment (sea water))	
CAS: 6153-56-6 oxalic acid		
PNEC	1.622 mg/l (sporadic release) 1,550 mg/l (STP) 0.1622 mg/l (water (fresh water)) 0.01622 mg/l (water (sea water))	
CAS: 5949-29-1 citric acid		
PNEC	33.1 mg/l (sewage plant) >1,000 mg/l (STP) 440 mg/l (water)	
PNEC	34.6 mg/kg (freshwater (Süßwasser)) 3.46 mg/kg (water (sea water))	

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 4)

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Protective gloves**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove materialValue for the permeation: Level 6 (≥ 480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Liquid

Colour:

Black

Odour:

Fruit-like

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

100 °C (CAS: 7732-18-5 water)

Flammability

Product is not flammable.

Lower and upper explosion limit**Lower:**

Not applicable

Upper:

Not applicable

Flash point:

Not applicable.

Auto-ignition temperature:

Not applicable.

Decomposition temperature:

Not determined.

pH at 20 °C

3.8-4.2

Viscosity:**Kinematic viscosity at 20 °C**

15-20 s (DIN 53211/4)

Dynamic:

Not determined.

Solubility**water:**

Fully miscible.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure at 20 °C:

23 hPa (CAS: 7732-18-5 water)

Density and/or relative density**Density at 20 °C:**1.06-1.07 g/cm³**Vapour density**

Not determined.

9.2 Other information**Appearance:****Form:**

Fluid

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Change in condition**Evaporation rate**

Not determined.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 5)

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Not corrosive to metals in line with 37.4 UN RTDG, handbook on test methods and criteria.
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity** No dangerous reactions known.
10.2 Chemical stability Stable under normal conditions.
10.3 Possibility of hazardous reactions No dangerous reactions known.
10.4 Conditions to avoid See Section 7 for information on safe handling.
10.5 Incompatible materials: strong oxidizing agents
10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Oral	ATE	>2,000 mg/kg (Additivity formula)
Dermal	ATE	>5,000 mg/kg (Additivity formula)

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Oral	LD50	>300 mg/kg (rat) (OECD 423 (Conc. 46%))
Dermal	LD50	1,000-2,000 mg/kg (rat) (OECD 402 (Conc. 98%))

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD 50	>5,000 mg/kg (rat)

CAS: 6153-56-6 oxalic acid

Oral	LD50	375 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

CAS: 5949-29-1 citric acid

Oral	LD50	3,000 mg/kg (rat)
------	------	-------------------

Primary irritant effect:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Values relevant for classification:

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 6)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 6153-56-6 oxalic acid

Oral | LOAEL | 150 mg/kg (rat) (OECD 407)

CAS: 5949-29-1 citric acid

Oral | NOAEL | 1,200 mg/kg (rat)

11.2 Information on other hazards

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

LC50 / 96h >100 mg/l (*Oncorhynchus mykiss*) (OECD 203 (Subs. thioglycolic acid))

LC50 / 48h 880 mg/l (*Leuciscus idus*) (DIN 38412 / 15 (Subs. thioglycolic acid))

EC50 / 48h 38 mg/l (*Daphnia magna*) (84/449/EWG (Subs. thioglycolic acid))

EC50 / 72h 13 mg/l (*Pseudokirchneriella subcapitata*) (OECD 201 (Subs. thioglycolic acid))

CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts

LC 50 >10-100 mg/l (*Leuciscus idus*)

EC0 >100 mg/l (*Pseudomonas putida*)

EC50 >100 mg/l (*Scenedesmus subspicatus*)

>10-100 mg/l (*Daphnia magna*)

NOEC >1-10 mg/l (*Leuciscus idus*)

>0.1-1 mg/l (*Daphnia magna*)

CAS: 6153-56-6 oxalic acid

LC50 / 96h 160 mg/l (fish)

EC50 / 48h 162.2 mg/l (*daphnia*) (OECD-Prüfrichtlinie 202)

EC50 / 72h 20.58 mg/l (*Pseudokirchneriella subcapitata*) (OECD 201)

CAS: 5949-29-1 citric acid

LC50 / 4 d 440-760 mg/l (*Leuciscus idus*) (OECD 203)

LC50 / 48h 440 mg/l (*Leuciscus idus*)

LC50 / 24h 1,353 mg/l (*Daphnia magna*)

EC50 / 16h 1,535 mg/l (*daphnia*)

EC50 / 24h 440 mg/l (*Leuciscus idus*)

EC50 / 72h 120 mg/l (*Daphnia magna*)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Biodegradation 67 % (28d OECD 301d (thioglycolic acid))

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 7)

CAS: 6153-56-6 oxalic acid

CSB	180 mg/g
BSB	160 mg/g
Biodegradation	89 %

CAS: 5949-29-1 citric acid

Biodegradation	97 % (OECD 301 B Ready Biodegradability - CO2 Evolution)
Biodegradation	98 % (OECD 302 B)

12.3 Bioaccumulative potential

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

log POW	>2.99 (20°C OECD 107 (thioglycolic acid))
---------	---

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 30	detergents other than those mentioned in 20 01 29
----------	---

15 01 02	plastic packaging
----------	-------------------

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR/RID/ADN Void
IMDG, IATA Void

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA
Class Void

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 8)

14.4 Packing group
ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:
Marine pollutant: No

14.6 Special precautions for user Not applicable.

UN "Model Regulation": Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

CAS: 1310-73-2 sodium hydroxide	12% of total caustic alkalinity
-----------------------------------	---------------------------------

European Directives:

Directive 2010/75/EU (VOC) not subject to

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 02.02.2026

Version: 7.00 (replaces version 6.01)

Revision: 20.10.2025

Trade name: SONAX Beast Wheel cleaner

(Contd. of page 9)

Classification according to Regulation (EC) No 1272/2008

Serious eye damage/irritation Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

Date of previous version: 22.04.2025**Version number of previous version:** 6.01**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**