



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx UL 18.0046**

Page 1 of 4

Certificate history:

Status: **Current**

Issue No: 1

[Issue 0 \(2018-10-24\)](#)

Date of Issue: 2021-12-20

Applicant: **Shenzhen CESP Co., Ltd.**
6th Fl Wangcheng Bldg.
Longhua St.
Longhua District
Shenzhen, Guangdong 518109
China

Equipment: **LED Surface-mounted Luminaires, CES-J200, CES-J100 and CES-J40s**

Optional accessory:

Type of Protection: **Increased Safety "ec"**

Marking: **Ex ec IIC T4 Gc**
-40°C ≤ Tamb ≤ +40°C

Approved for issue on behalf of the IECEx
Certification Body:

Katy A. Holdredge

Position:

Senior Staff Engineer

Signature:
(for printed version)

Date:
(for printed version)

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

UL LLC
333 Pfingsten Road
Northbrook IL 60062-2096
United States of America





IECEx Certificate of Conformity

Certificate No.: **IECEx UL 18.0046**

Page 2 of 4

Date of issue: 2021-12-20

Issue No: 1

Manufacturer: **Shenzhen CESP Co., Ltd.**
6th Fl. Wangcheng Bldg.
Longhua St.
Longhua District
Shenzhen, Guangdong 518109
China

Manufacturing
locations: **Shenzhen CESP Co., Ltd.**
(Dongguan Branch)
No. 273 Tangxia South Road
Fenghuanggang
Tangxia Town
Dongguan City, Guangdong
China

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2011 Explosive atmospheres - Part 0: General requirements
Edition:6.0

IEC 60079-7:2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

US/UL/ExTR18.0054/00

US/UL/ExTR18.0054/01

Quality Assessment Report:

NO/DNV/QAR21.0015/00



IECEX Certificate of Conformity

Certificate No.: **IECEX UL 18.0046**

Page 3 of 4

Date of issue: 2021-12-20

Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

NOTE: This certificate was temporarily SUSPENDED over the period of 2021-05-26 to 2021-11-18 at the request of the issuing IECEx Certification Body (ExCB) following their consultation with the Applicant. This suspension does NOT affect products manufactured prior to 2021-05-26 or after 2021-11-18. Any product manufactured during the suspension period of 2021-05-26 to 2021-11-18 cannot be considered to be IECEx Certified under this Certificate. Any comment may be directed to the Applicant or ExCB.

CES-J200, CES-J100 and CES-J40s series of luminaires are composed of Glass Diffuser, LED Module, Seal Ring, LED Housing with Diffuser Cover as a LED compartment, LED Driver, Power Seal Ring, Driver Housing with Bottom Cover as a LED Driver Compartment, and Connection Seal Ring between LED compartment and Driver compartment. The constructions of all housings including LED Housing and Driver Housing, Seal Rings and Glass Diffuser that fully enclosure of LED module and LED driver are evaluated for "ec" protection. All housings and covers are die-cast aluminum alloy, the diffuser is glass and secured to diffuser cover. There are two Seal Rings secured between the glass housing, driver housing respectively. The equipment is LED (light emitting diode) luminaire intended for surface-mounted installation.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: NO



IECEX Certificate of Conformity

Certificate No.: **IECEX UL 18.0046**

Page 4 of 4

Date of issue: 2021-12-20

Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Issue 1: Updates QAR to NO/DNV/QAR21.0015/00. No ExTR update.

Annex:

[Annex to IECEx UL 18.0046 Issue 1.pdf](#)



IECEx Certificate of Conformity

Certificate No.: IECEx UL 18.0046

Issue No.: 1

Page 1 of 1

PARAMETERS RELATING TO THE SAFETY

CES-J200 series, rated 110~277 Vac, 50/60 Hz, 2.1 A;

CES-J100 series, rated 110~277 Vac, 50/60 Hz, 1.2 A;

CES-J40s series, rated 110~277 Vac, 50/60Hz, 0.43 A.

MARKING

Marking has to be readable and indelible; it has to include the following indications:

For IECEx:

Manufacturer: Shenzhen CESP Co., Ltd Add.: 6th Fl. Wangcheng Bldg., Longhua St., Longhua District, Shenzhen, Guangdong, China Equipment: LED Luminaires Model No.: CES-J40S Rated Current: 0.43A -40°C ≤ T_{amb} ≤ +40°C Serial No. XXXX Input Volt: 110-277VAC Date Code: 2017-04-27 IECEx UL 18.0046 Ex ec IIC T4 Gc WARNING - THE LUMINAIRE SHALL NOT BE OPENED	Manufacturer: Shenzhen CESP Co., Ltd Add.: 6th Fl. Wangcheng Bldg., Longhua St., Longhua District, Shenzhen, Guangdong, China Equipment: LED Luminaires Model No.: CES-J100 Rated Current: 1.2A -40°C ≤ T_{amb} ≤ +40°C Serial No. XXXX Input Volt: 110-277VAC Date Code: 2017-04-27 IECEx UL 18.0046 Ex ec IIC T4 Gc WARNING - THE LUMINAIRE SHALL NOT BE OPENED	Manufacturer: Shenzhen CESP Co., Ltd Add.: 6th Fl. Wangcheng Bldg., Longhua St., Longhua District, Shenzhen, Guangdong, China Equipment: LED Luminaires Model No.: CES-J200 Rated Current: 2.1A -40°C ≤ T_{amb} ≤ +40°C Serial No. XXXX Input Volt: 110-277VAC Date Code: 2017-04-27 IECEx UL 18.0046 Ex ec IIC T4 Gc WARNING - THE LUMINAIRE SHALL NOT BE OPENED
---	--	--