



The sharpest in the team.

The **Forstner EASY** is the ultimate machinery for sheet metal work in the construction industry. Set the lengths and quantity with the user friendly control system. The sheet metal feeds smoothly into the machine and is straightened and cut with fantastic precision and burr-free edges. Coils instead of blanks is a money and space efficient solution that frees up space, money and time as well as minimizing waste.

The most important advantages:

- ✓ Small but extremely powerful
- ✓ 3 roller manual straightener
- ✓ Smart, user-friendly control system
- ✓ High in-feed speeds
- ✓ Easy to use settings



The control touch screen has uncomplicated and user-friendly commands. Here you control all the functions of the machine.



The EASY series has 3 manual straightening rollers to remove coil set and give customers flat material every time. The rollers are made of polished steel with a 70 mm diameter. The pressure of the straightening rolls is set by locking handles with reference scale.



If you want to prepare your line for a film applicator, then the option with the fully rubberized rollers is ideal for you. This means that your line is ideally prepared for retrofitting a film applicator at any time and with ease



The infeed guide roller are angled to match the loop of the coil from a decoiler. This helps prevent creasing on soft materials like copper, aluminum and zinc.



The table guide has four roller bearings (two on each side) to guide the metal in the pinch rolls. The roller bearings allow the metal to move easily forward and backwards without damaging the edges. This also keeps the material straight as the material is fed into the machine helping to ensure a square cut.



Optional: The film applicator can basically be mounted on any table. Using the deflection rollers and the fully rubberized feed rollers, the protective film is pressed on almost bubble and wrinkle-free. The decive type F-AG z2mo has an additional arm with tension spring for tensioning the film during the return movement. This design is only applicable for single decoiling systems. The film applicator is available in both 50" (1250 mm) and 59" (1500 mm).

Machine	Туре	Working width	Cutting capacity - Steel 400 N/mm ²	Cutting capacity - Stainless steel 600 N/mm²	Cutting capacity - Aluminum 200 N/mm²	Shear
		mm	mm	mm	mm	
EASY PRO 1250	Cut to length	1250	1.5	1	1.8	Guillotine shear
EASY CUT 1250	Cut to length	1250	1	0.6	1.2	Roller shear

Dealer

