



Small in size but big in output.


The Forstner STRAIGHT range are highly efficient machines for cutting from coil. The machines have double feeding rollers making in-feed easier and changesovers faster. An easy-to-adjust straightening unit with six rollers gives you flat blanks for further production regardless of material type or thickness. Speeds are up to a full 25 meters per minute for highly efficient production. Equipped with a guillotine shear the machine is fast, requires minimal maintenance and gives you perfect cutting surfaces. The entire process is easily handled with the logical control system SPS-S1.

The most important advantages:

- ✓ Compact design
- ✓ Stable construction
- Guillotine shear for optimal cutting surface and faster processing
- ✓ Ideal for sensitive materials
- ✓ Easy to use and multi-function control system



The control touch screen has uncomplicated and user-friendly commands. Here you control all the functions of the machine.



The STRAIGHT machine has 6 manual straightening rollers to remove coil set and give customers flat material every time.



The infeed guide roller are angled to match the loop of the coil from a decoiler. This helps prevent creasing on soft materials like copper, aluminum and



The table guide has four roller bearings (two on each side) to guide the metal in the pinch rolls. The roller bearings allow the metal to move easily forward and backwards without damaging the edges. This also keeps the material straight as the material is fed into the machine helping to ensure a square cut.



Optional: The film appicator can basically be mounted on any table. Using the deflection rollers and the fully rubberized feed rollers, the protective film is pressed on almost bubble and wrinkle-free. The device type F-AG z2mo has an additional arm with tension spring for tensioning the film during the return movement. This design is only applicable for single decoiling systems.



Optional: The coil guide is an important component for the function and accuracy of every system. The table has a fixed and a manually adjustable coil guide with ball bearings. The adjustment of the movable coil guide is done by a hand wheel. This specific table has rollers integrated in the table to ensure a smooth surface.

Machine	Туре	Working width	Straightening rolls Ø	Cutting capacity Steel 400 N/mm ²	Cutting capacity Stainless Steel 600 N/mm ²	Speed	Shear
		mm	mm	mm	mm	m/min	
STRAIGHT CUT 1250	Straight & Cut-to-Length	1250	70	1.0	0.6	max. 25	Roller shear
STRAIGHT PRO 1250	Straight & Cut-to-Length	1250	70	1.5	1.0	max. 25	Guillotine shear
STRAIGHT CUT 1500	Straight & Cut-to-Length	1500	70	1.0	0.6	max. 25	Roller shear
STRAIGHT PRO 1500	Straight & Cut-to-Length	1500	70	1.2	1	max. 25	Guillotine shear

Dealer

