

AUGUSTA 4081



CHARACTERISTICS

- Made of 12 mm diameter polyamide kernmantle rope lifeline including a steel karabiner (opening 18 mm) and a steel scaffolding hook (opening 50.8 mm)
- Wear-resistant eye to protect loops from damage
- The attachment of the lifeline is secured with a strong transparent cover sheath that protects the end, making the stitches visible for easy inspection
- Length: 1 metre
- Strength: 22 kN

Article number: 8.84.081.00

SUITABLE FOR WORK IN, E.G.:

- Scaffolding
- Construction
- Installation technology
- Aerial platforms
- Offshore
- Petrochemicals

PACKAGING

- 1 piece per polybag
- 5 pieces per case

CE 0598
EN 354:2010

ITEM INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PIECE (POLYBAG)	EAN CODE 25 PIECES (CASE)
One size	8.84.081.00	8718249047428	8718249047435

STORAGE REQUIREMENTS

During transport, keep the lanyard in its bag, well away from any cutting surface. Clean it with water, wipe it with a rag and hang it up in a well-ventilated location, to let it dry naturally and away from a naked flame or heat source; follow the same procedure for components that have become damp during use. The lanyard should be stored in its bag in a warm, dry, well-ventilated location. Keep it well away from all heat sources.

TESTING INSTITUTE

This fall protection is certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, please refer to the following web link:
www.oxxa-safety.com/doc

RELATED PRODUCTS



4012 HARNESS 5D

Harness 5D
Article no. 8.84.012.00



ELBERT 4082

Positioning rope XL 1.5 m
Article no. 8.84.082.00



HAYES 4083

Positioning rope XL 2 m
Article no. 8.84.083.00

YOUR SUPPLIER: