



COLD



LIQUID PROOF



GRIP

X-FROST

51-860



TOUCHSCREEN



15.HPK.63284
Hohenstein HTI

CHARACTERISTICS

- Glove with HPT® (Hydropellent Technology) coating on the palm and fingers
- Nylon liner (15 gauge) and a terry acrylic lining (7 gauge)
- Seamless glove with elastic knitted wrist cuff
- The $\frac{3}{4}$ HPT® coating continues all the way to the knuckles for extra protection
- Excellent grip under both wet and dry conditions
- The brushed inner liner is soft and comfortable and keeps your hands warm when working in cold conditions
- Both the liner and the coating are water repellent
- Extremely supple and flexible glove with an excellent fit, even at low temperatures
- Sanitised to inhibit bacterial growth, minimize odours and encourage freshness
- The conductive coating on the fingers ensures that all touchscreen devices can be operated perfectly
- Free from harmful substances in accordance with OEKO-TEX® Standard 100

Article number: 1.51.860.00

SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Scaffolding
- Government services
- Transport & logistics
- Recycling
- Civil and hydraulic engineering
- Agriculture
- Cold activities

COLOUR

Black/grey

SIZES

8/M to 11/XXL incl.

PACKAGING

- 1 pair per headercard
- 12 pairs per bundle
- 72 pairs per outer box

EN388:2016
+A1:2018



3X31B

EN511:2006



X2X

EN407:2020



X1XXXX



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
8/S	1.51.860.08	8718249037856	8718249037863	8718249037870
9/L	1.51.860.09	8718249035630	8718249035647	8718249035654
10/XL	1.51.860.10	8718249035661	8718249035678	8718249035685
11/XXL	1.51.860.11	8718249035692	8718249035708	8718249035715

CLARIFICATION OF PICTOGRAMS

EN388:2016

+A1:2018



3X31B

EN388:2016

+A1:2018



ABCDEF

Protection against mechanical hazards

A = Scuff resistance (0-4)

B = Cut resistance (0-5)

C = Tear resistance (0-4)

D = Puncture resistance (0-4)

E = Cut resistance (in accordance with EN ISO 13997 (A to F))

F = Impact resistance (optional) (P = Passed)

EN407:2020



X2XXXX

EN407:2020



ABCDEF

Protection against heat and fire hazards

A = Limited flame spread (0-4)

B = Contact heat (0-4)

C = Convection heat (0-4)

D = Radiant heat (0-4)

E = Small drops of molten metal (0-4)

F = Large drops of molten metal (0-4)

EN511:2006



X2X

EN511:2006



ABC

Protection against cold

A = Radiant Cold (0-4)

B = Contact Cold (0-4)

C = Water Resistance (0-1)

Note: X = Not tested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: SATRA Technology Europe Ltd (Notified Body no. 2777), Bracetown Business Park, Clonee, Dublin D15 YN2P, Ireland.

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa.work/doc

YOUR SUPPLIER:

RELATED PRODUCTS



X-GRIP-THERMO
51-850

Art. no. 1.51.850.00



X-PRO-WINTER-DRY
51-870

Art. no. 1.51.870.00