

MDIN20W series

20W Constant Voltage Din Rail Power Supply



■ Features:

- Constant voltage design
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Cooling by free air convection
- Can be installed on DIN Rail TS-35/7.5 or 15
- Universal input voltage range
- DC ok signal (Open collector type)

CE SELV LPS

⊗ ELECTRICAL SPECIFICATION

MODEL	MDIN20W12	MDIN20W24
OUTPUT		
Rated Voltage	12V	24V
Rated Current	1.67A	1A
Current Range	0 ÷ 1.67A	0 ÷ 1A
Rated Power	20W	24W
No Output Voltage (max.)	12.6V	25.2V
Voltage Adjustment Range [6]	11 – 13.80V	21 – 28V
Line Regulation	± 0.5%	
Load Regulation	± 2%	
Voltage Tolerance [3]	± 5%	
Ripple & Noise (max.) [2]	280mV _{p-p}	
Setup, Rise Time [4]	max. 820ms, max. 70ms / 230VAC at full load	
Hold up Time (typ.)	65ms / 230VAC at full load	
INPUT		
Voltage Range	90 ÷ 264VAC	
Frequency Range	47 ÷ 63Hz	
Efficiency (typ.)	80%	82%
AC current (typ.)	0.15A / 230VAC, 0.42A / 115VAC,	
Inrush current (max.)	60A / 230VAC(25°C)	
No Load Power Consumption (max.)	1W	
PROTECTIONS		
Over Current	Range: 110 ÷ 145%	
	Type: hiccup mode. Recovers automatically after fault condition is removed.	
Short Circuit	Type: hiccup mode.	
Over Voltage	14 ÷ 17V	28 ÷ 31V
	Type: shut down output voltage. Re-power on to recovery.	
Over Temperature	Range: 110°C ± 10°C	
	Type: shut down output voltage. Re-power on to recovery.	
WORKING ENVIRONMENT		

Working Temperature	-20°C ÷ +50°C
Working Humidity	45 ÷ 85% RH non-condensing
Storage Temperature and Humidity	-30°C ÷ +70°C, 10 ÷ 95% RH non-condensing

SAFETY AND EMC REGULATIONS

Safety Standards	Compliance to EN62368-1
Withstand Voltage	IN/OUT: 3kVAC, IN/GND: 2kVAC, OUT/GND: 0.5kVAC
EMC Emission	Compliance to EN55032
EMC Immunity	Compliance to EN55024
Harmonic Current	Compliance to EN61000-3-2, EN61000-3-3

OTHERS

Dimensions	100 x 94 x 23mm (L x W x H)	
Weight and Packing	0.15kg	
EAN Code		

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.

2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.


3. Tolerance includes set up tolerance, line regulation and load regulation.

4. Setup and rise time is measured from 0 to 90% rated output voltage.

5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

6. By built-in potentiometer.

Ⓢ MECHANICAL SPECIFICATION



PIN ASSIGNMENT			
No.	Assignment	No.	Assignment
1	Input: GND	5	Output: U _{OUT} -
2	Input: AC/N	6	Output: DC OK
3	Input: AC/L	7	U _{OUT} Potentiometer
4	Output: U _{OUT} +		