

The **ROSadhesive** (= a waterbased acrylic dispersion adhesive) is a versatile bonding and grout system to install the **ROS Design Tiles** on mineral surfaces such as natural stone-/brickwork, concrete, plasterboard and organic surfaces such as wood, chipboard, MDF, plywood and uPVC. The solvent-free **ROSadhesive** cures by evaporation of water and forms a strong, durable, moisture resistant bonding.

Please note, these instructions only provide general information and general recommendations for the use of ROSadhesive. It is provided for informational purposes only. It is imperative that in case of any doubt you should seek independent advice from (local) certified professionals regarding the use, application and installation of this product. Local building codes need to be checked to ensure that the application of this product agree with good building practices.

Coverage:

1 cartridge (content: 310 ml) is sufficient to install appr. 1.5-2 m² **ROS Design Tiles**.

Shelf-life:

12 months. Once opened the shelf-life will be limited. Storage: dry location between +5°C and +25°C.

Safety & Health:

- The **ROSadhesive** is not classified as dangerous according to the EU directive 1994/45/EC. Nevertheless keep the cartridge out of the reach of children. Avoid contact with the eyes and skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed or in case you feel unwell seek medical advice immediately and show this packaging or label.

Limitations:

- Not recommended for locations subject to water immersion and not for PE, PP, Teflon and bituminous surfaces.
- Do not apply or allow to dry at ground and air temperatures below +15°C or above +40°C.
- The temperature resistance after curing is between -15°C and +60°C.

Wall preparation and installation:

- Make sure the surface is level, sturdy, clean, dry, free of loose debris, cracks, dust and grease or oil. Surface consistency and suitability must be judged on site and is your own responsibility. In case of any doubt obtain professional advice.
- Put the **ROSadhesive** all around on the back of the Design Tile to about 1-3 mm away from the edge, with an equal thickness of the adhesive. In addition apply the corners with an extra dot of adhesive of an average of 2 cm. On the remaining surface spread evenly minimum 3 – parallel – stripes of adhesive. **Follow the installation guidelines of the ROS Design Tile manual.**
- The processing time is 5-10 minutes.
- Paintable after 24 hours. Reaches its final adhesion within one week after application.
- Clean the used tools with fresh water.

A full Product Data Sheet is available at www.rebelofstyles.com