

Before you start

READ THESE INSTRUCTIONS CAREFULLY AND COMPLETELY BEFORE USING THE PRODUCT.

Please ensure that these instructions only contain general information and recommendations for use by REBEL OF STYLES (subsequently: ROS). These instructions are purely informative. In case of doubt, you must seek independent advice from authorised personnel (on site) regarding the use, application and installation of this product. Check the local building regulations to ensure that the use of this product meets the requirements for proper construction.

- The **ROS UltraFlex** serves only as a decorative wall covering for indoor and outdoor areas, unless otherwise stated on the packaging.
- Avoid any kind of surface contamination when handling, as it may be difficult to remove.
- We recommend the use of our specially developed products: Primer = Klimex Primer; special glue = KlimexCol.
- Use the correct (and clean) tools when handling. We recommend using a spirit level, a serrated trowel / spreader, a ruler, a pencil, a paintbrush and a pair of scissors.
- Keep the **ROS UltraFlex**-product clean during installation. If you spill glue on the UltraFlex - Products, they should be cleaned immediately and carefully with a damp cloth dipped in clean water.
- UltraFlex products are resistant to temperatures up to a maximum of + 70 ° C.
- Place the product at a temperature between +5 ° C to + 28 ° C.

Substrate

- Ensure that the substrate is solid, flat, viable, stressless, clean, dry and free of dust, grease, oil, dirt or separating layers (such as wallpaper or paint). Carry out all necessary preparations to the wall's surface, such as cleaning, repairing damage to the surface, removing loose layers (e.g. wallpaper) and paint/coatings, repairing, evening out and priming plaster.
- Not suitable for direct application on: vapour-permeable, porous, bituminous, EPS / XPS and woody surfaces.
- The surface must be flat and straight and must not contain irregularities of more than 2 mm.
- Warning! Walls freshly plastered with gypsum must be sanded down and dusted before being worked on. Priming is required for this type of application.
- The assessment regarding the condition and suitability of the substrate must take place on site and is your responsibility. In case of doubt, seek specialist advice.

Applying products

- We recommend using our specialty glue product KlimexCol or a similar specialty glue suitable for attaching this product. Seek an on-site specialist/retailer for advice on this.
- Before applying the products, check that the place where you are going to install the products is level. To do this, apply a vertical stop to the wall, possibly using a wooden slat or a metal profile.
- ! UltraFlex products are applied from top to bottom !
- Always check the products thoroughly before handling them. Always display an amount of product near the work area first. This helps determine the correct distribution and makes the application faster. Always select and mix products from different boxes to get an even pattern of colors, sizes, textures and shapes. Size corrections can easily be made with a pair of scissors.
- Spread the KlimexCol adhesive evenly over the surface of the wall with an 8mm serrated trowel as much as can be covered with the strips in 15 minutes.
- Then press the brick slips firmly into the glue. Start at the top and work your way down gradually. Try to keep the width of the joints around 10 mm for best results.

- Smooth the joints with a damp brush immediately after applying the brick slips. Make sure that there are no openings or cracks, so that moisture cannot get behind the stone strip.
- Trimming the products: To ensure the ROS UltraFlex-products line up well next to each other, you can trim/shorten them using a pair of scissors.
- Stresses on the substrate or the UltraFlex-product must be avoided.

Maintenance & cleaning

- When cleaning, do not use acidic products, chemical detergents or steel brushes as they may damage the surface.
- Use a clean, soft – and perhaps slightly damp – cloth for cleaning.

General information

- **ROS UltraFlex** may, unless otherwise stated on the packaging, be used indoor and outdoor. The products must not be used under water. Avoid walls subject to strong temperature fluctuations. If in doubt, seek professional advice from your supplier.
- Dimensions: All dimensions are nominal and subject to manufacturing tolerances. We are continuously engaged in the innovation and improvement of our products. ROS therefore reserves the right to change designs and specifications without prior notice.
- Color: The UltraFlex-product is a natural product and can naturally or under the influence of the climate have variations in color and shade. Therefore, an identical and uniform color cannot be guaranteed. These variations emphasize however the natural appearance of ROS products and do not affect the suitability of the products. When using multiple boxes, always select and mix products from different boxes to get an even pattern of colors, sizes, textures and shapes.
- Conditions: In the unlikely event that you are dissatisfied with the condition in which the products reach you, you must immediately notify the dealer. Please note: if you apply a product that has been identified with defects in advance, we are not responsible for any costs resulting from the use of these defective products. Although we do our utmost best to provide you with optimal advice, ROS is not responsible for any loss, damage or injury caused by following this advice. We disclaim any liability if products have been used for purposes other than for which they are intended, or if damage is caused due to our advice not being followed.

Health & safety

Always first read the instructions for use and the guidelines for the product you are using. In case of doubt, always seek specialist advice first.