

Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 1 of 11

True Cast Resin

SECTION 1: Chemical product and company identification

Product identifier

Product name: True Cast Resin

Product code: FLTCLV01

Recommended use of the product and restriction on use

Relevant identified uses: For use in Formlabs SLA Printers.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Formlabs, Inc

35 Medford St

Suite 201 Somerville, MA 02143

+1 617 855 0762

sds@formlabs.com

Emergency telephone number:

APAC

CHEMTREC (APAC)

+65 3163 8374 (24/7)

SECTION 2: Hazards identification

Classification in accordance with JIS Z 7252:2019 and the GHS Revision 6:

Skin irritation, category 2

Eye irritation, category 2A


Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3, respiratory tract irritation

Chronic aquatic hazard, category 2

Label elements

Hazard pictograms:



Signal Word: Warning

Hazard statements:

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H411 Toxic to aquatic life with long lasting effects

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 2 of 11

True Cast Resin

P272 Contaminated work clothing should not be allowed out of the workplace
P273 Avoid release to the environment
P280 Wear protective gloves, protective clothing and eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 Call a doctor or physician if you feel unwell.
P332+P313 If skin irritation occurs: Get medical advice/attention
P333+P313 If skin irritation or rash occurs: Get medical advice/attention
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing
P363 Wash contaminated clothing before reuse
P391 Collect spillage
P403+P233 Store in a well-ventilated place. Keep container tightly closed
P405 Store locked up
P501 Dispose of contents and container in accordance with local, regional, national, and international regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Substance: Not applicable

Mixture:

Identification	Name	Wt. %
CAS number: Trade Secret	Methacrylate oligomer(s)	40-60
CAS number: 72869-86-4	Urethane dimethacrylate	15-25
CAS number: 43048-08-4	Methacrylate monomer(s)	25-45
CAS number: 75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	<2

Additional information: None

SECTION 4: First-aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory symptoms develop or persist, seek medical advice/attention.

After skin contact:

Wash affected area with plenty of soap and water. Remove contaminated clothing and laundry before reuse. If skin irritation develops or persists, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so.



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 3 of 11

True Cast Resin

Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning and tearing.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation may have adverse effects on the respiratory tract. Symptoms may include cough, breathing difficulties, sore throat and inflammation of the mucous membrane lining the respiratory tract.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate medical attention and special treatment

Specific treatment:

If respiratory symptoms persist, seek medical attention.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA).

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways.

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 4 of 11

True Cast Resin

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Safe packaging material

Suitable material:

Not determined or not applicable.

Unsuitable material:

Not determined or not applicable.

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

No occupational exposure limits noted for the ingredient(s).

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 5 of 11

True Cast Resin

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Dark purple
Odor	Characteristic acrylate.
pH	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	> 100°C
Flash point (closed cup)	> 93.5°C
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not flammable.
Lower flammability/explosive limit	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Relative density	Not determined or not available.
Relative gas density	Not determined or not available.
Density	1.07 g/cm ³
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Particle characteristics	Not determined or not available.
Solubilities	Not determined or not available.

Other information

Dynamic viscosity	174 cP (25°C), 104 cP (35°C).
-------------------	-------------------------------

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Stable under recommended handling and storage conditions.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 6 of 11

True Cast Resin

Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

Incompatible materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Hazard information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Urethane dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg
Methacrylate monomer(s)	oral	LD50 Rat: > 2000 mg/kg
	dermal	LD50 Rat: > 2000 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg ([No mortality occurred])
Methacrylate oligomer(s)	oral	LD50 Rat: 3300 mg/kg

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
Methacrylate monomer(s)	Causes skin irritation.
Methacrylate oligomer(s)	Causes skin irritation.

Serious eye damage/irritation

Assessment:

Causes serious eye irritation.

Product data:

No data available.

Substance data:

Name	Result
Methacrylate monomer(s)	Causes serious eye irritation.
Methacrylate oligomer(s)	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data:



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 7 of 11

True Cast Resin

Name	Result
Urethane dimethacrylate	May cause an allergic skin reaction.
Methacrylate monomer(s)	May cause an allergic skin reaction.
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	May cause an allergic skin reaction.
Methacrylate oligomer(s)	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Name	Classification
Urethane dimethacrylate	Not Applicable
Methacrylate monomer(s)	Not Applicable
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Not Applicable
Methacrylate oligomer(s)	Not Applicable

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Suspected of damaging fertility.

Specific target organ toxicity (single exposure)

Assessment:

May cause respiratory irritation.

Product data:

No data available.

Substance data:

Name	Result
Methacrylate monomer(s)	May cause respiratory irritation.
Methacrylate oligomer(s)	May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 8 of 11

True Cast Resin

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Urethane dimethacrylate	Fish LC50 Danio rerio: 10.1 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 1.2 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: 0.68 mg/L (72 hr [growth rate])
Methacrylate monomer(s)	Fish LC50 Danio rerio: 0.144 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 2.63 mg/L (48 hr [read-across])
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Fish LC50 Cyprinus carpio: 1.4 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 3.53 mg/L (48 hr [immobilisation])
	Aquatic Plants EC50 Raphidocelis subcapitata: >2.01 mg/L (72 hr [growth rate])

Chronic (long-term) toxicity**Assessment:**

Toxic to aquatic life with long lasting effects.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Urethane dimethacrylate	The substance is not readily biodegradable (22% degradation in 28 days).
Methacrylate monomer(s)	The substance is not readily biodegradable based on test results for an analogous substance. 28.1% degradation in water after 28 days.
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	The substance is not readily biodegradable. 0-10% degradation in water, measured by O2 consumption, after 28 days.



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 9 of 11

True Cast Resin

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Methacrylate monomer(s)	The substance is expected to bioaccumulate in organisms. BCF (aquatic species): 1 493 L/kg ww
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	The substance is not expected to bioaccumulate (BCF: 72 dimensionless, aquatic species: Cyprinus carpio).

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Urethane dimethacrylate	The substance has moderate potential to adsorb to organic soil and sediment particles (log Koc: 3.66 dimensionless).
Methacrylate monomer(s)	This substance moderate potential to be adsorbed by the soil.
Methacrylate monomer(s)	The substance is slightly mobile in soil with a high potential for adsorption to soil and sediment. Koc at 20 °C: 8674
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	The substance is moderately mobile, therefore, there is moderate potential for adsorption to soil and sediment (log Koc: 2.895, QSAR substance data).

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB..

Substance data:

PBT assessment:

Urethane dimethacrylate	This substance is not PBT.
Methacrylate monomer(s)	This substance is not PBT.
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	The substance is not PBT.

vPvB assessment:

Urethane dimethacrylate	This substance is not vPvB.
Methacrylate monomer(s)	This substance is not vPvB.
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	The substance is not vPvB.

Hazard to the ozone layer

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Notes on disposal

Disposal methods:

Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 10 of 11


True Cast Resin

Contaminated packages:


Dispose contaminated packages in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information


International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of <5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Maritime Dangerous Goods (IMDG)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of <5L provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Urethane dimethacrylate
UN transport hazard class(es)	9 
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of ≤5L provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
-----------	------



Safety Data Sheet

According to Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6

Initial preparation date: 02.21.2025

Page 11 of 11

True Cast Resin

Ship type	None
Pollution category	None

SECTION 15: Regulatory information

Japan regulations

Japan Inventory of Existing and New Chemical Substances (ENCS): All ingredients are listed or exempt.

Chemical Substance Control Law

Priority Assessment Chemical Substance: None of the ingredients are listed.

Industrial Safety and Health Act (ISHA)

Existing Chemical Substances:

72869-86-4	Urethane dimethacrylate	Listed	2-(5)-212
43048-08-4	Methacrylate monomer(s)	Listed	7-(1)-530
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Listed	4-(3)-48, 4- (3)-0048
Trade Secret	Methacrylate oligomer(s)	Listed	(7)-1438

Ordinance on Prevention of Organic Solvent Poisoning: None of the ingredients are listed.

PRTR Specified Class 1 Substances: None of the ingredients are listed.

PRTR Class 1 Substances: None of the ingredients are listed.

PRTR Class 2 Substances: None of the ingredients are listed.

Poisonous and Deleterious Substances: None of the ingredients are listed.

Fire Service Law:

72869-86-4	Urethane dimethacrylate	Not Applicable
43048-08-4	Methacrylate monomer(s)	Not Applicable
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Not applicable.
Trade Secret	Methacrylate oligomer(s)	Not applicable.

Additional information:

Fire Service Law: Flammable liquid, Class 4, Petroleum 3, Water-insoluble liquid, Danger class III, 2000 liters.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with Japanese National Standard JIS Z 7252:2019, JIS Z 7253:2019 and the GHS Revision 6 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 02.21.2025

End of Safety Data Sheet

