



TECHNICAL SPECIFICATION

Print technology	FFF (fused filament fabrication)	Max. head temperature	500°C
Build volume XYZ	530 x 530 x 530 mm	Max. platform temperature	180°C
Chamber	Enclosed, isolated and actively heated	Max. chamber temperature	140°C
Min. layer height	50 µm	Built-in filament dryer for 4 spools	Yes (max. 4 x 3 kg), up to 80°C
Build Platform	Heated, easily removable and replaceable PEI surface	Automatic change of filaments	Yes
Number of printing heads	2 - electronic lifting system	Built-in accessory drawer	Yes
Drive type	X, Y, Z axes - ball screw drives; all drives with encoders	Communication	SD Card, Ethernet, WiFi, USB
Nozzle diameter	0,2 - 1,2 mm	Control	10.1" LCD, website, camera
Filament diameter	1,75 mm	Software	Orca Slicer
Max. printing speed	90 cm³/h	Predefined print settings	Yes, for Omni3D filaments and Omni3D approved filaments.
Positioning accuracy	+/- 1.56 µm. in all axes (theoretical)	Supported files	.stl, .obj, .3mf, .gcode, .factory
Printed part accuracy	+/- 0.12% (not less than +/- 0.12mm)	Power	230V / 50Hz (optionally 110 V / 60 Hz)
Automatic platform calibration	Yes	Max. power consumption	3,6 kW
Air filtration	CARBON + HEPA	Printer dimensions	160 x 110 x 150 cm
		Printer weight	440 kg



Headquartered in Poland, Omni3D is an **industrial-first manufacturer** specializing in high-temperature FDM systems. We deliver **certified production ecosystems** for Aerospace, Defense, and Automotive sectors. Our heritage in precision engineering ensures that every Omni3D unit acts as a bridge between CAD design and **functional, end-use reality**.

Ecosystem Features

Tangible ROI

Up to 90% cost savings on tooling and spare parts. Replace CNC-machined aluminum and steel components with high-strength polymers, achieving 80% weight reduction and a dramatic **reduction in Total Cost of Ownership**.

Full Thermal Control

Dimensional **accuracy** at scale. A precision-regulated build environment maintains uniform cooling rates across the entire build volume, eliminating internal stress, warping, and tolerance drift in large-format industrial components.

140°C Heated Chamber

Engineered for **PA CF, PC-ABS, and PEKK**. Sustained high-temperature environment ensures superior Z-axis bonding and isotropic strength, producing structural end-use parts with mechanical properties rivaling injection molding.

Patented liquid-cooled printhead

24/7 reliability at extreme temperatures. Our proprietary cooling system eliminates heat creep and filament jamming, enabling continuous high-temperature extrusion with zero thermal fluctuation or hardware degradation.

Filament Monitoring and Drying

Material integrity guaranteed. Automated sensors detect flow anomalies and end-of-spool events, while the integrated drying system **keeps hygroscopic materials moisture-free**, ensuring optimal tensile strength and zero-waste production.

45+ tested and preset materials

First-time-right results, every time. Choose from a library of 45+ tested industrial polymers with optimized presets, delivering **complete application flexibility and immediate compatibility** with demanding engineering requirements.

TCMS - Technical Condition Monitoring System)

Full process visibility. Real-time telemetry tracks every thermal gradient and mechanical movement remotely. Complete **traceability and reporting** built for ISO-certified production workflows.

Automated Build Plate Calibration

Repeatable precision. Zero setup errors. High-resolution surface mapping guarantees a perfect first layer every time, removing human error from the workflow so your engineers focus on design, not machine leveling.



Fundusze Europejskie
Inteligentny Rozwój



Rzeczpospolita
Polska



Unia Europejska
Europejski Fundusz
Rozwoju Regionalnego



www.omni3d.com

Contact our application
team for a technical
assessment or ROI analysis.
sales@omni3d.com





Headquartered in Poland, Omni3D is an **industrial-first manufacturer** specializing in high-temperature FDM systems. We deliver **certified production ecosystems** for Aerospace, Defense, and Automotive sectors. Our heritage in precision engineering ensures that every Omni3D unit acts as a bridge between CAD design and **functional, end-use reality**.

Ecosystem Features

Tangible ROI

Up to 90% cost savings on tooling and spare parts. Replace CNC-machined aluminum and steel components with high-strength polymers, achieving 80% weight reduction and a dramatic **reduction in Total Cost of Ownership**.

Full Thermal Control

Dimensional **accuracy** at scale. A precision-regulated build environment maintains uniform cooling rates across the entire build volume, eliminating internal stress, warping, and tolerance drift in large-format industrial components.

140°C Heated Chamber

Engineered for **PA CF, PC-ABS, and PEKK**. Sustained high-temperature environment ensures superior Z-axis bonding and isotropic strength, producing structural end-use parts with mechanical properties rivaling injection molding.

Patented liquid-cooled printhead

24/7 reliability at extreme temperatures. Our proprietary cooling system eliminates heat creep and filament jamming, enabling continuous high-temperature extrusion with zero thermal fluctuation or hardware degradation.

Filament Monitoring and Drying

Material integrity guaranteed. Automated sensors detect flow anomalies and end-of-spool events, while the integrated drying system **keeps hygroscopic materials moisture-free**, ensuring optimal tensile strength and zero-waste production.

45+ tested and preset materials

First-time-right results, every time. Choose from a library of 45+ tested industrial polymers with optimized presets, delivering **complete application flexibility and immediate compatibility** with demanding engineering requirements.

TCMS - Technical Condition Monitoring System)

Full process visibility. Real-time telemetry tracks every thermal gradient and mechanical movement remotely. Complete **traceability and reporting** built for ISO-certified production workflows.

Automated Build Plate Calibration

Repeatable precision. Zero setup errors. High-resolution surface mapping guarantees a perfect first layer every time, removing human error from the workflow so your engineers focus on design, not machine leveling.



www.omni3d.com

Contact our application team for a technical assessment or ROI analysis.
sales@omni3d.com

