

WOODGUARD REVITALIZER - 5170

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : WOODGUARD REVITALIZER
Product code : 5170.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaning product Wood

1.3. Details of the supplier of the safety data sheet

Registered company name : GUARD INDUSTRIE S.A.S..
Address : 7 Rue Gutenberg,93100.Montreuil.France.
Telephone : 0155861760. Fax : 0148581689.
info@guardindustrie.com
www.guardindustrie.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Hazard statements :

H314

Causes severe skin burns and eye damage.

Precautionary statements - Prevention :

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

P264

Wash hands thoroughly after handling.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.



WOODGUARD REVITALIZER - 5170

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or a doctor.
P321 In case of visiting a doctor, show the MSDS.
P363 Wash contaminated clothing before reuse.
Precautionary statements - Disposal :
P501 Dispose of contents/container to a centre for harmful waste.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 607_006_00_8 CAS: 144-62-7 EC: 205-634-3 OXALIC ACID	GHS07 Wng Acute Tox. 4, H302 Acute Tox. 4, H312	[1]	10 \leq x % < 25
INDEX: BIF AMMONIUM CAS: 1341-49-7 EC: 215-676-4 REACH: 01-2119489180-38-xxxx BIFLUORURE D'AMMONIUM	GHS06, GHS05 Dgr Acute Tox. 3, H301 Skin Corr. 1B, H314 STOT SE 3, H335		0 \leq x % < 1
INDEX: 603-024-00-5 CAS: 123-91-1 EC: 204-661-8 1,4-DIOXANE	GHS02, GHS08, GHS07 Dgr Flam. Liq. 2, H225 Carc. 2, H351 Eye Irrit. 2, H319 STOT SE 3, H335 EUH:019-066	D [1] [2]	0 \leq x % < 1

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Move victims into fresh air.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.



WOODGUARD REVITALIZER - 5170

Wash with water and soap. if any sign/symptom develops seek for medical assistance.

In the event of swallowing :

Do not give the patient anything orally.
Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :
- multipurpose ABC powder

Unsuitable methods of extinction

In the event of a fire, do not use :
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- fluorine (F₂)

5.3. Advice for firefighters

Refresh with water the closed containers exposed to fire.
Remove all sources of ignition.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an alkaline decontaminant, such as an aqueous solution of sodium carbonate or similar.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.



WOODGUARD REVITALIZER - 5170

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3	VME-ppm	VLE-mg/m3	VLE-ppm	Notes
144-62-7	1	-	-	-	-
123-91-1	73	20	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
144-62-7	1 mg/m3	2 mg/m3	-	-	-
123-91-1	20 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME	VME	Excess	Notes
123-91-1	20 ml/m3	73 mg/m3	2(I)	DFG, H

- France (INRS - ED984 :2008) :

CAS	VME-ppm	VME-mg/m3	VLE-ppm	VLE-mg/m3	Notes	TMP No
144-62-7	-	1	-	-	-	-
123-91-1	20	73	40	140	C2	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA	STEL	Ceiling	Definition	Criteria
144-62-7	1 mg/m3	2 mg/m3	-	-	-
123-91-1	25 ppm	100 ppm	-	-	-

Predicted no effect concentration (PNEC):

BIFLUORURE D'AMMONIUM (CAS: 1341-49-7)

Environmental compartment: Soil.
PNEC : 22 mg/kg

Environmental compartment: Fresh water.

WOODGUARD REVITALIZER - 5170

PNEC :	1.3 mg/l
Environmental compartment: PNEC :	Waste water treatment plant. 76 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)
- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection



WOODGUARD REVITALIZER - 5170

N/A

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Important health, safety and environmental information

pH : Not stated.
Strongly acidic.

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : > 1
Method for determining the density :
ISO 3507 (Laboratory glassware - Pycnometers).

Water solubility : Soluble.

Viscosity : 14 mm²/s < v <= 20,5 mm²/s (40°C)

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

Keep away from :

- bases

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)
- fluorine (F₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

WOODGUARD REVITALIZER - 5170

11.1.1. Substances

Acute toxicity :

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

Oral route : LD50 = 130 mg/kg
Species : Rat

Dermal route : LD50 > 375 mg/kg
Species : Rat
Other guideline

OXALIC ACID (CAS: 144-62-7)

Oral route : LD50 = 500 mg/kg
Species : Rat

Dermal route : LD50 = 1100 mg/kg
Species : Rat

Skin corrosion/skin irritation :

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

Corrosivity : Causes severe skin burns.

Germ cell mutagenicity :

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

No mutagenic effect.

Carcinogenicity :

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

Carcinogenicity Test : Negative.
No carcinogenic effect.

Reproductive toxicant :

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

No toxic effect for reproduction

11.1.2. Mixture

Skin corrosion/skin irritation :

Corrosive classification is based on an extreme pH value.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

BIFLUORIRE D'AMMONIUM (CAS: 1341-49-7)

Fish toxicity : EC50 mg/l
Species : *Salmo gairdneri*
Duration of exposure : 96 h

NOEC = 4 mg/l

Crustacean toxicity : EC50 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h



WOODGUARD REVITALIZER - 5170

	NOEC = 8.9 mg/l Species : Daphnia magna Duration of exposure : 21 days
Algae toxicity :	EC50 mg/l Duration of exposure : 96 h
OXALIC ACID (CAS: 144-62-7) Fish toxicity :	LC50 = 160 mg/l Species : Leuciscus idus Duration of exposure : 48 h
Crustacean toxicity :	EC50 = 136.9 mg/l Species : Daphnia magna Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

BIFLUORURE D'AMMONIUM (CAS: 1341-49-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

OXALIC ACID (CAS: 144-62-7)

Biodegradability : Rapidly degradable.
DBO5/DCO = 0.89

12.3. Bioaccumulative potential

12.3.1. Substances

OXALIC ACID (CAS: 144-62-7)

Octanol/water partition coefficient : log K_{ow} = -0.81

Bioaccumulation : BCF = 0.6

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

WOODGUARD REVITALIZER - 5170

Soiled packaging :

Empty container completely. Keep label(s) on container.
Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

20 01 29 * detergents containing dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

3265

14.2. UN proper shipping name

UN3265=CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
(bifluorure d'ammonium)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C3	II	8	80	1 L	274	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	II	1 L	F-A,S-B	274	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.



WOODGUARD REVITALIZER - 5170

- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : nonionic surfactants

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H302 + H312	Harmful if swallowed or in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer .
EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.