

## IN2-MASTIC



### PRODUCT DESCRIPTION


#### MASTIC FOR REPAIRING CRACKS AND SPALLS IN NATURAL STONE AND CONCRETE

Polishable mastic for filling holes in concrete and natural stone. Without chemicals that damage the surface.

Once hardened, it equals or improves the hardness and toughness of the treated stone, admitting its polishing perfectly.

#### STANDARD COLOURS

Black  
Dak grey  
Light grey  
Beige  
White  
Neutral



#### COLOUR ON DEMAND



IN2-MASTIC can be produced in all possible colours.



### ADVANTAGES IN2-MASTIC

- + *Hardens the treated stone*
- + *High resistance to weather influences and solvents*
- + *Low shrinkage, high adhesion*
- + *Well polishable and grindable*
- + *Low amount of styrene*



### HOW TO USE

Make sure the surface that needs to be glued is thoroughly cleaned and completely dry.

Mix the glue with 2-3% drying paste (dosage: 100 parts glue + 3 parts hardener) to achieve a perfect binding. Hardening time: 3-7 minutes at 25°C with 3% hardener.

Apply the product and wait until it is completely hardened before grinding.



### SPECIAL CONSIDERATIONS

- Contains: styrene
- The customer is responsible to verify the suitability of the product before use and to verify that the use of the product is done according to laws, legislation and patents of the customer's country.

#### TECHNICAL INFO

Shape	Colored liquid
Flashpoint	Not relevant
Viscosity	15000 - 19000 cps at 25°C
Ratio of use glue / hardener	100 parts glue + 2/3 parts hardener
Gel time	3 / 4 minutes at 25°C
Tacky free	After 15-20 minutes in thin layer at 25°C
Packaging	Tin cans of 1,5 kg
Storage	Keep the cap tightly closed and store in a cool place at 20°C
Storage life	IN2-MASTIC can be kept at least 6 months at 25°C



### HEALTH AND PROTECTION

Safety isn't expensive, it's priceless. Always work safe!



- Wear safety shoes, safety glasses, gloves, a helmet and other protective clothing.
- When working with chemicals, wear a mouth mask.
- Avoid excessive breathing of vapors or mists, especially in poorly ventilated areas.
- Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.
- When feeling unwell or experiencing irritation on skin, eyes or inhalation, consult a doctor immediately.
- Consult the MSDS for more detailed information.



### TECHNICAL SUPPORT

Technical questions? Contact your local distributor.

Distributor stamp

IN2-CONCRETE  
info@in2-concrete.com