

Hydraulic Drive EHTX44Y5



This high performance eight foot class machine is powered by a 44-HP Yanmar turbo diesel engine. With a top rotor speed of 140 RPM this trowel sets the standard for both ease of use and performance.



- **Hydrostatic drive** supplies optimum power to each rotor assembly for reliable performance. It reduces service costs by eliminating maintenance items such as belts, clutches and gearboxes.
- Non-overlapping rotors are powered by independent drive motors that consistently deliver the high torque required for pan applications.
- **Retardant spray system** is actuated by controls located on the steering handles for uniform coverage of the slab surface.
- Adjustable seat features armrests and provides essential back support. All controls and warning lights are convenient to the operator.
- Automatic shut-down beneath the seat stops the rotors from turning if the operator stands up while the engine is running.
- **Proportional hydraulic steering** has been enhanced and offers improved responsiveness with minimal effort on the part of the operator.
 - Twin Pitch control is standard for fast, accurate blade pitch adjustments

Specifications BLADES PATH FUEL TANK OPERATING **LxWxH** ENGINE ROTOR кw WHEEL ENGINE MODEL PER WIDTH CAPACITY WEIGHT (HP) RPM КІТ COOLING CM (IN) ROTOR CM (IN) LTR (GAL) KG (LBS) 32.8 318 X 165 X 145 YANMAR EHTX44Y5 LIQUID 5 10-140 233 (92) 42 (11) 841 (1885) EMR3 TURBO (44) (95 X 48 X 59)

