

# IN2-CONCRETE

## IN2-WASHOUT+



### PRODUCT DESCRIPTION

#### SURFACE RETARDANT FOR DESACTIVATED CONCRETE


IN2-WASH-OUT+ is a budget and environment friendly water based surface retardant for a positive application of de-activated concrete. It creates an exposure depth of 3 mm.

IN2-WASH-OUT+ has been developed for bulk applications and works the best on large surfaces. It's optimized for all weather conditions thanks to the integrated curing compound and for concrete mixtures with Dmax 16 mm. The active ingredients migrate into the concrete and slow down the cement reaction.



### ADVANTAGES IN2-WASHOUT+

- + Budget friendly
- + Surface retardant and curing compound in one
- + Eco friendly
- + Protects against sun and wind



### HOW TO USE

IN2-WASHOUT+ is optimized for concrete mixtures with Dmax 16mm. Do not use on mixtures with aggregates that are too small.

Place the fresh concrete without leaving marks and spray IN2-WASHOUT+ on the surface with a sprayer or sprinkler. Allow the concrete to cure. Wash out between 12 and 24 hours after application, depending on climatic conditions. Rinse off the product with a high-pressure cleaner.

**Consumption:**  $\pm 5\text{m}^2/\text{kg}$ , ensure that the entire surface has been covered well. Using too much product is not harmful, but using more will not accelerate the effect.



### SPECIAL CONSIDERATIONS

- Solvent free product
- Don't dump in sewer, surface water or ground water
- Contains biocides: bronopol (INN), mixture of: 5-Chloro-2-Methyl-2H-isothiazol-3-one [EC No. 247-500-7] and 2-Methyl-2H-iso-thiazole-3-one [EC No. 220-239-6] (3:1). May cause allergic reaction.

### TECHNICAL INFO

Shape	White liquid
Flash point	$>100^\circ\text{C}$
pH (20°C)	$>2$
Density (20°C)	1,02 g/cm <sup>3</sup>
Water	83,7 %
Boiling point	100 °C
Vapor pressure (20°C)	23 hPa
Reactions	No dangerous reactions are known
Dilution	Use neat. Do not dilute.
Consumption	$\pm 5\text{m}^2/\text{kg}$ ; Using too much is not harmful but will not accelerate the working.
Storage	Store between 5°C and 35°C, don't put in direct sunlight and keep the container tightly closed.
Storage life	IN2-WASHOUT+ can be stored for 12 months in the original container.



### HEALTH AND PROTECTION

Safety isn't expensive, it's priceless. Always work safe!



- Wear gloves and protective clothing.
- Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.
- When feeling unwell or experiencing irritation on skin, eyes or inhalation, consult a doctor immediately.
- Consult the MSDS for more detailed information.



### TECHNICAL SUPPORT

Technical questions? Contact your local distributor.

Distributor

IN2-CONCRETE

info@in2-concrete.com



Scan me

WWW.IN2-CONCRETE.COM

Order online

PDS

MSDS

Application video

PDS IN2-WASHOUT+ - last edited 14/06/2019