

iQparts
IQ-PARTS-SHOP.COM



**SPECS &
INFORMATION**



Special hose made of two-ply PVC with coated spring steel spiral and additional axial and radial yarn reinforcement. This design and unique manufacturing process give this type of hose special properties, making it a highly popular quality product.

Temperature range

0 °C to 85 °C

Application ranges

, Drying of buildings, Drying screed, Weld fume suction, PVC hoses, Suction hoses, dusts and powder, Suction hoses, small shavings and solids, Dust removal, Building cleaning, Household vacuum cleaners, Industrial vacuum cleaners, Cleaning machines, Suction and pressure hose, Dust suction, Vacuum cleaners, Drying buildings, , Elastic hose, highly

Variant/Detailed View/Recommended connectors



Length

Standard length: 15 m, from Ø 70 = 10 m. Other lengths upon request.

Properties

- Highly flexible
- Yarn reinforced
- Largely smooth interior
- Lightweight
- Durable/long service life
- Non-kinking
- Very high tensile strength
- Vacuum-resistant
- Tear-resistant
- Good resistance to leach and acids
- Good UV resistance and ozone resistance
- Good chemical resistance
- Smallest bending radii
- Good vacuum tightness
- Conductive when spiral is grounded
- Free of cadmium in accordance with BGR 132
- Wall thickness up to Ø 70 : 0,65 mm

Miscellaneous

Bestselling product.
Made in Germany.



iq
parts
IQ-PARTS-SHOP.COM

info@iq-parts.nl
Harsweg 34A
2431 EZ Ter Aar
T +31 252 624 126
The Netherlands