

iQ parts
IQ-PARTS-SHOP.COM





**SPECS &
INFORMATION**



THE PULL-RING SYSTEM

Pull-rings



QUICK CONNECT

Pull-rings with a U-shaped seal, in conjunction with the pipe components indicated in the catalogue, shock explosion proof tested up to 3 bar.

PULL-RING WITHOUT SEALANT

3060

- Pull-rings for use in conjunction with U-shaped seal for 1 and 2 mm pipework system
- From DN 80 to 300 mm, shock explosion proof to 3 bar
- Pull-ring for 3 mm wall thickness, in conjunction with U-shaped seal made of NBR or silicone for 2 mm pipe-work system
- Please also read and take into account the technical information given at the beginning of this chapter

Pull-rings for 1 and 2 mm wall thickness

Pull-rings for 3 mm wall thickness

DN	A	B	kg	Electro-galvanised	Stainless steel	C	E	Electro-galvanised	Stainless steel
				Item no.	Item no.			Item no.	Item no.
60	81	60	0.30	12062383	12063383				
80	101	80	0.31	12082383	12083383				
100	125	104	0.33	12102383	12103383				
120	145	124	0.36	12122383	12123383	151	126	12122926	12123926
140	161	140	0.37	12142383	12143383				
150	175	154	0.39	12152383	12153383	181	156	12152926	12153926
175	200	179	0.42	12172383	12173383	206	181	12172926	12173926
200	225	204	0.45	12202383	12203383	231	206	12202926	12203926
224	245	224	0.47	12222383	12223383				
250	275	254	0.51	12252383	12253383	281	256	12252926	12253926
280	302	281	0.55	12282383	12283383				
300	325	304	0.57	12302383	12303383	331	306	12302926	12303926
315	337	316	0.58	12312383	12313383				
350	375	354	0.63	12352383	12353383	381	356	12352926	12353926
400	425	404	0.68	12402383	12403383	431	406	12402926	12403926
450	478	450	0.73	12452383	12453383				
500	524	500	0.78	12502383	12503383				
560	586	560	0.83	12562383	12563383				
630	656	632	0.90	12632383	12633383				



info@iq-parts.nl
Harsweg 34A
2461 EZ Ter Aar
T +31 252 624 126
The Netherlands