


**iQ parts**  
IQ-PARTS-SHOP.COM



**SPECS &  
INFORMATION**

# BALL-LOKT™ TIES



**Ball-Lok™ Ties unique buckle design is the globally accepted industry standard.**

- Four widths – 0.18" (4.6mm), 0.31" (7.9mm), 0.47" (12mm), and 0.59" (15mm) for applications ranging from identification tagging to bundling large cables
- Self locking design allows fast installation
- Installation with hand tool to assure uniform tension and clean tail cut-off for safe handling
- Available in Type 304 and Type 316 stainless steels to provide good to excellent corrosion resistance in a wide variety of environments
- Coated Ball-Lok™ Ties are fully coated with black epoxy

| Part Number           | Material        | Width  |      | Length |      | Base Material Thickness |       | Maximum Diameter Single Wrap |      | Minimum Loop Tensile Strength lbs | Package Quantity | Application Tools |  |
|-----------------------|-----------------|--------|------|--------|------|-------------------------|-------|------------------------------|------|-----------------------------------|------------------|-------------------|--|
|                       |                 | In     | mm   | In     | mm   | In                      | mm    | In                           | mm   |                                   |                  |                   |  |
| <b>Ball-Lok™ Ties</b> |                 |        |      |        |      |                         |       |                              |      |                                   |                  |                   |  |
| <b>Coated</b>         | <b>Uncoated</b> |        |      |        |      |                         |       |                              |      |                                   |                  |                   |  |
|                       | KT4U046-0200    | 304 SS | 0.18 | 4.6    | 7.9  | 200                     | 0.010 | 0.25                         | 2.0  | 52                                | 100              | 100               | CB1000<br>C07569<br>K50289<br>XE9229<br>or by hand |
|                       | KT4U046-0250    | 304 SS | 0.18 | 4.6    | 9.8  | 250                     | 0.010 | 0.25                         | 2.7  | 67                                | 100              | 100               |  |
|                       | KT4U046-0350    | 304 SS | 0.18 | 4.6    | 13.8 | 350                     | 0.010 | 0.25                         | 3.9  | 99                                | 100              | 100               |  |
|                       | KT4U046-0500    | 304 SS | 0.18 | 4.6    | 19.7 | 500                     | 0.010 | 0.25                         | 5.8  | 147                               | 100              | 100               |  |
| KT6B046-0200          | KT6U046-0200    | 316 SS | 0.18 | 4.6    | 7.9  | 200                     | 0.010 | 0.25                         | 2.0  | 52                                | 100              | 100               |  |
| KT6B046-0250          | KT6U046-0250    | 316 SS | 0.18 | 4.6    | 9.8  | 250                     | 0.010 | 0.25                         | 2.7  | 37                                | 100              | 100               |  |
| KT6B046-0350          | KT6U046-0350    | 316 SS | 0.18 | 4.6    | 13.8 | 350                     | 0.010 | 0.25                         | 3.9  | 99                                | 100              | 100               |  |
| KT6B046-0500          | KT6U046-0500    | 316 SS | 0.18 | 4.6    | 19.7 | 500                     | 0.010 | 0.25                         | 5.8  | 147                               | 100              | 100               |  |
|                       | KT4U078-0200    | 304 SS | 0.31 | 7.9    | 7.9  | 200                     | 0.010 | 0.25                         | 2.0  | 52                                | 175              | 100               |  |
|                       | KT4U078-0250    | 304 SS | 0.31 | 7.9    | 9.8  | 250                     | 0.010 | 0.25                         | 2.7  | 67                                | 175              | 100               |  |
|                       | KT4U078-0350    | 304 SS | 0.31 | 7.9    | 13.8 | 350                     | 0.010 | 0.25                         | 3.9  | 99                                | 175              | 100               |  |
|                       | KT4U078-0500    | 304 SS | 0.31 | 7.9    | 19.7 | 500                     | 0.010 | 0.25                         | 5.8  | 147                               | 175              | 100               |  |
|                       | KT4U078-0600    | 304 SS | 0.31 | 7.9    | 23.6 | 600                     | 0.010 | 0.25                         | 7.0  | 179                               | 175              | 100               |  |
| KT6B078-0200          | KT6U078-0200    | 316 SS | 0.31 | 7.9    | 7.9  | 200                     | 0.010 | 0.25                         | 2.0  | 52                                | 175              | 100               |  |
| KT6B078-0250          | KT6U078-0250    | 316 SS | 0.31 | 7.9    | 9.8  | 250                     | 0.010 | 0.25                         | 2.7  | 67                                | 175              | 100               |  |
| KT6B078-0350          | KT6U078-0350    | 316 SS | 0.31 | 7.9    | 13.8 | 350                     | 0.010 | 0.25                         | 3.9  | 99                                | 175              | 100               |  |
| KT6B078-0500          | KT6U078-0500    | 316 SS | 0.31 | 7.9    | 19.7 | 500                     | 0.010 | 0.25                         | 5.8  | 147                               | 175              | 100               |  |
| KT6B078-0600          | KT6U078-0600    | 316 SS | 0.47 | 12     | 23.6 | 600                     | 0.010 | 0.35                         | 7.0  | 179                               | 175              | 100               |  |
| KT6B120-0450          | KT6U120-0450    | 316 SS | 0.47 | 12     | 17.7 | 450                     | 0.014 | 0.35                         | 5.2  | 131                               | 250              | 100               |  |
| KT6B120-0550          | KT6U120-0550    | 316 SS | 0.47 | 12     | 21.7 | 500                     | 0.014 | 0.35                         | 6.4  | 163                               | 250              | 100               |  |
| KT6B120-0600          | KT6U120-0600    | 316 SS | 0.47 | 12     | 23.6 | 600                     | 0.014 | 0.35                         | 7.0  | 179                               | 250              | 100               |  |
| KT6B150-0500          | KT6U150-0500    | 316 SS | 0.59 | 15     | 19.7 | 500                     | 0.014 | 0.35                         | 5.8  | 147                               | 325              | 50                |  |
| KT6B150-0600          | KT6U150-0600    | 316 SS | 0.59 | 15     | 23.6 | 600                     | 0.014 | 0.35                         | 7.0  | 179                               | 325              | 50                |  |
| KT6B150-0700          | KT6U150-0700    | 316 SS | 0.59 | 15     | 27.6 | 700                     | 0.014 | 0.35                         | 8.3  | 211                               | 325              | 50                |  |
| KT6B150-0750          | KT6U150-0750    | 316 SS | 0.59 | 15     | 29.5 | 750                     | 0.014 | 0.35                         | 9.6  | 243                               | 325              | 50                |  |
| KT6B150-0900          | KT6U150-0900    | 316 SS | 0.59 | 15     | 35.4 | 900                     | 0.014 | 0.35                         | 10.8 | 274                               | 325              | 50                |  |
| KT6B150-1100          | KT6U150-1100    | 316 SS | 0.59 | 15     | 43.3 | 1100                    | 0.014 | 0.35                         | 13.3 | 338.2                             | 325              | 50                |  |

**304 316**





info@iq-parts.nl  
Harsweg 34A  
2461 EZ Ter Aar  
T +31 252 624 126  
The Netherlands