

ALASKA 210 START



ELEMENTS *Tronic*

12V

24V

Wet

Gel

MF

AGM

Pb-Ca

EFB

NEW

- Battery charger and trickle charger with TRONIC technology for 12/24V lead batteries for motorbikes, cars, vans, etc.
- Automatic charging and maintenance in Tronic at 12/24V. 12V starting.
- Advanced charging and maintenance functions for EFB, AGM and low temperature.
- Digital display for voltage, current and charge percentage. Warning LED to indicate battery charge status and- end of charge;
- Protection against overloads and polarity reversal.

DESCRIPTION

Electronic battery charger and trickle charger with TRONIC technology for WET, GEL, AGM, MF, PbCa, EFB batteries at 12V/24V.-

12V starter.

Advanced charging and maintenance functions for EFB, AGM and low temperature batteries.

Display for voltage, current, and charge percentage.




Features:

- Automatic charging and maintenance in Tronic at 12/24V;
- 12V starting;
- Advanced charging and maintenance functions for EFB, AGM and low temperature ;
- Digital display for voltage, current and charge percentage ;
- Warning LED to indicate battery charge status and -end of charge;
- Protection against overloads and polarity reversal.

Complete with cable with clamps.



TECHNICAL DATA

CODE	CODE 807579	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P	CHARGING ABSORBED POWER 300 W	P_{START}	STARTING ABSORBED POWER 2,2 kW		CHARGE AND STARTING VOLTAG. 12 / 24 V
A_{EFF}	EFFECTIVE CHARGING CURRENT 25 / 12 A	A_{EN}	RATED CHAR.CUR.EN60335-2-29 15 / 8 A	A_{1V/C}	START CUR.1V/C EN60335-2-29 100 A
A_{START MAX}	MAX STARTING CURRENT 150 A		MIN.RATED REFERENCE CAPAC. 10 / 10 Ah		MAX.RATED REFERENCE CAPAC. 300 / 160 Ah



ADJUSTMENT POSITIONS
5



DIMENSIONS (LxWxH)
24,5 x 19,5 x 13 cm



WEIGHT
7,57 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



CERTIFICATE