Sophisticated RIP software maximizes the performance of UJF-7151 plus

Raster Link 5

User friendly RIP key features

- Easy to follow icons enable intuitive and user-friendly operation
- Related settings feature in one window to simplify RIP operations, with 'Register as Favourite' option available for regularly used layouts
- · Printing progress can be monitored on the

Additional useful functions

1. JIG & Template function

Registration of templates is achieved through a 'JIG layout function' parameter in RasterLink 6, allowing the designed image to be placed inside the template layout procedure and accurately positioned for print setup and registration of image file.

2. Web update function

Program update and profile download can be easily performed via the internet.

Specifications

Item		UJF-7151 plus	
Printhead		On-demand piezo head (6 staggered printheads)	
Maximum print resolution		1,200dpi	
Maximum printable area		710 × 510mm	
Ink	Type/Colour	LH-100 (C, M, Y, K, W, Cl) PR-200 (Primer)	
	Package size	1L bottle	
Media	Size	710 × 510mm or smaller	
	Height	153mm or less	
	Weight	10kg or less	
Certifications		VCCI class A, FCC class A, ETL UL 60950-1 CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star	
Interface		USB 2.0 Hi-speed / Ethernet 1000BASE-T	
Power supply		Single-phase AC100 - 120V / AC200 - 240V	
Power consumption		1.3 kW	
Operational environment		Temperature: $15-30^{\circ}\text{C}$ Humidity: $35-65\%$ Rh (Non condensing) Recommended temperature range for stable operation: $20-25^{\circ}\text{C}$	
Dimensions (W × D × H)		2,198 × 1,572 ×1,273mm	
Weight		317kg (Base stand weight is included)	

Note: Data in the above specifications are subject to change without notice.

You are dealing with UV light sources that may harm your health. Please follow below guidelines strictly:

- . Do not look directly into the UV light source nor place your hand, or expose your skin directly to the UV light source.
- Depending upon print mode, there might occur some VOC emittance from printed parts not yet cured and hardened.
- Please read and follow the instructions and guidelines of the manual carefully.



www.mimakieurope.com info@mimakieurope.com @MimakiEurope



Supplies

Item	Colour	Item No.	Remarks
	Cyan	LH100-C-BA	Volume per bottle 1 Litre
	Magenta	LH100-M-BA	
111.400	Yellow	LH100-Y-BA	
LH-100	Black	LH100-K-BA	
	White	LH100-W-BA	
	Clear	LH100-CL-BA	
PR-200	Primer	PR200-Z-BA-1	

Inks and substrates:

- Please note that properties and adhesion, weather resistance etc. of ink and substrates can vary. Therefore please test materials before printing.
- Some substrates require primer before printing. Please test materials beforehand or ask your sales representative











PRELIMINARY BROCHVIRE

[•] Some of the samples in this folder are artificial renderings • Specifications, design and dimensions stated in this folder may be subject to change without notice (for technical improvements, etc.)

of the printing heads, also note that if using multiple printer units, colours could vary slightly from one unit to other unit due to slight individual differ



state-of-the-art technology to deliver a powerful and reliable digital alternative to traditional screen print operations.

Mimaki

Next-generation direct-to-object production flatbed LED UV printer

Capitalising on its peerless heritage in compact UV LED direct-to-object print technology, the UJF-7151 plus reaffirms Mimaki's market dominance in this

rapidly developing sector. Geared to on-demand printing of the very highest quality at industrial production levels of output, UJF-7151 plus utilises

ENGINEERING EXCELLENCE AND CREATIVE INNOVATION

Founded in Japan in 1975, Mimaki Engineering has steadily grown by reputation and influence into a global company with large operational bases in Asia and the Pacific, United States and Europe.

hardware, software and associated consumable items, such as inks and cutting blades

· · · Mimaki delivers

UJF-7151 plus delivers ···

- Precise ink drop placement at up to 1.200dpi
- 6 staggered print heads
- Large 710 x 510mm printable area
- Superior image quality control technology (MAPS4 & MFD1)
- Direct printing on substrates up to 153mm thick
- High-end industrial construction for precision production output
- Process. White & Clear inks. plus Primer
- High speed printing up to twice the speed of previous models

UV LED CURING 710 x 510mm MAX. PRINT AREA MAX. MEDIA THICKNESS 153mm 1 LITRE INK BOTTLE SUPPLY USB2.0 / ETHERNET 1000 INTERFACE LOW POWER CONSUMPTION

reduces ink settling and

In addition, the system

removes air bubbles.

which plug the nozzle.

requency is thereby a more cost-effective

and stable print output.

Nozzle-cleaning

ovides stable ink jetting.

UJF-7151 plus



High performance and high productivity

The 710 x 510mm print bed accommodates most commonly used traditional screen print sizes, making this machine an ideal upgrade for traditional screen printers.

An array of six staggered printheads increases the printing speed to approximately twice the speed of previous models and approximately 2.6 times that of competitive models. This gives



Create ··· Promotional items, Personalised giftware, Bespoke products, Control panels, Pens, Packaging, Small-medium format rigid signage, Instrumentation & Gauge faces, Custom components, Branded electronic device cases and covers and much more...

KEY TECHNICAL FEATURES · · ·


High quality industrial construction

In order to reduce printer unit vibration, the print table moves during printing instead of the Y-bar Two ball screws are installed on both sides of the table to assist with its movement. In addition, four motor-driven leas are added beneath the table to maintain its horizontal position when the table is lifted or lowered, resulting in a more precise droplet placement and higher quality print output



4. Uninterrupted printing features

In the event of a nozzle malfunction not being repairable by the use of the maintenance function, printing can continue by the use of another nozzle, without any loss of productivity or a reduction in image quality.



MAPS4 Advanced Pass System

Mimaki's unique anti-banding feature, MAPS4 is a more advanced version of MAPS3. To prevent banding, swath boundaries are overprinted and boundaries prone to banding are printed with fewer ink droplets.



MFD1-Mimaki Fine Diffusion 1

Dithering is an image processing technique, which transforms image data for inkjet printing Pattern and error-diffusion dithering may, however, generate particular image noise resulting in uneven colour printing or tone jumps, even on a high-performance printing unit.

patented* image-processing MFD1, which reduces noise due to dithering through hybrid processing of pattern- and error-diffusion dithering, thereby enhancing print quality.

MFD1 is available for Version 4.0 and higher

SUPERIOR IMAGE QUALITY CONTROL TECHNOLOGY · · ·



colour printing is delivered without noise.