

KUM803-2DM

280308-P

Marine and Land Based MF/HF Antenna. Receive Only
8m. 3 sections. Coaxial installation. Deck mount. Packed in a plastic bag

The antenna is a 3-section omnidirectional side-fed HF transceiver antenna for automatic antenna tuned systems for both commercial vessels and leisure. The antenna is manufactured in premium quality materials in order to prevent galvanic corrosion. Radiating elements are made of copper. The antenna is manufactured using crimping technology giving the antenna a 4-5 times stronger build-up. Installation via the integrated deck mount. The antenna has been sold worldwide for more than five decades. The antenna is subject for improvement at all times. The antenna has the same rugged design as all other AC Antennas products thus it withstands harsh environmental conditions, both...

Short description

| | |
|---------------|-----------------|
| Product group | HF/SSB |
| Design | Wire antenna |
| Pattern | Omnidirectional |

Electrical specifications

| | |
|-----------------------------|------------------------|
| Frequency range [MHz] | 0.15-30 |
| Bandwidth [MHz] | 29.85 |
| Max. Input Power [Watt] | Receive only |
| Max. HF Voltage [Kv] | |
| Insulation Resistance [Ohm] | >10 E9 |
| Static Capacitance [pF] | 100 |
| Polarisation | Vertical |
| DC Shorted | Yes |
| DC Grounded | Yes |
| Connector | Side Feed Bolt M8x1.25 |

Mechanical specifications

| | |
|--|--------------------------|
| Length [m/ft] | 7.88 / 25.90 |
| Sections | 3 |
| Weight [kg/lbs] | 8.00 / 17.70 |
| Survival Wind Speed [km/h / m/s / mph] | 200 / 44 / 124 |
| Wind Area [m2/ft2] | 0.2018 / 2.1722 |
| Wind Load @ 160km/h [N] | 293 |
| Material | Fibreglass |
| Colour | White |
| Operating Temperature Range [°C/°F] | -55 to +60 / -67 to +140 |
| Ingress Protection | IP66 |
| Thread | / - |
| Mounting | Deck mount integrated |



