

SPYDER

07-12-2015

1.0 LED

LED 7/10W | 350-500mA | 18Vf | COB 3-step | excl. power supply

CE IP20 960°C 0,3m 36° 85° 355°

white texture
white texture + black

124161W_
124161E_

LIGHT COLOUR

2700K | >90CRI | 420-590lm 3
3000K | >90CRI | 470-640lm 5

ALWAYS USE

for power supplies see our catalogue

1.0 PAR16

PAR16 max. 50W | GU10 | 220-240VAC | 50-60Hz

CE IP20 960°C 0,9m 85° 355° DO NOT COVER


white texture
white texture + black

124120W0
124120E0


ALWAYS USE

for PAR16 lamps see our catalogue


SAFETY DISTANCE FOR HALOGEN LAMPS





①




③



④



DIMENSIONS




MOUNTING INSTRUCTION

- ① Make a hole in the ceiling according to the prescribed dimensions.


POWER CONNECTION

- ② SERIAL CONNECTION - for LED

Always use **POWER SUPPLY** according to the specifications of the LED-module



PARALLEL CONNECTION - for PAR16



- ③ Insert the fixture in the hole. The lens of the SPYDER can be rotated without rotating the trim border.
- ④ Insert the lamp and fix with spring into the inner part.



WEVER & DUCRÉ
LIGHTING

www.weverducre.com

INSTALLATION
INSTRUCTIONS