



# Bring The Sun Home

Comfort and savings with our residential and commercial inverters

[www.goodwe.com](http://www.goodwe.com)



**GOODWE**  
YOUR SOLAR ENGINE

# Products Strengths



Start-up Voltage @50V



Highest Efficiency up to 98.3%

**30%**

30% DC Oversizing

**10%**

10% AC Overloading



Higher Power Density & Easy Installation



Compatible with double-glass bifacial modules

# Project Cases



6KW | Istanbul, Turkey



8KW | Antonio, Switzerland



4.5KW | Berwickshire, UK



4.5KW | Sao Paulo, Brazil



12KW | Cape Town, South Africa



3KW | Amsterdam, Holland

# XS Series

Single MPPT, Single Phase



Technical Data	GW700-XS	GW1000-XS	GW1500-XS	GW2000-XS	GW2500-XS	GW3000-XS
<b>PV String Input Data</b>						
Max. DC Input Power (W)	910	1300	1950	2600	3250	3900
Max. DC Input Voltage (V)	500	500	500	500	500	500
MPPT Range (V)	40~450	40~450	40~450	40~450	40~450	40~450
Start-up Voltage (V)	50	50	50	50	40	40
Nominal DC Input Voltage (V)	360	360	360	360	360	360
Max. Input Current (A)	11	11	11	11	12.5	12.5
Max. Short Current (A)	13.8	13.8	13.8	13.8	15.6	15.6
No. of MPP Trackers	1	1	1	1	1	1
No. of Input Strings per Tracker	1	1	1	1	1	1
<b>AC Output Data</b>						
Nominal Output Power (W)	700	1000	1500	2000	2500	3000
Max. Output Apparent Power (VA)	800	1100	1650	2200	2750	3300
Nominal Output Voltage (V)	230	230	230	230	230	230
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	3.5	4.8	7.2	9.6	12	14.3
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)					
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%	<3%
<b>Efficiency</b>						
Max. Efficiency	97.2%	97.2%	97.3%	97.5%	97.4%	97.4%
European Efficiency	96.0%	96.4%	96.6%	97.0%	97.0%	97.0%
<b>Protection</b>						
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
<b>General Data</b>						
Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Convection					
Noise (dB)	<25	<25	<25	<25	<25	<25
User Interface	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED
Communication	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN	WiFi or LAN
Weight (kg)	5.2	5.2	5.2	5.2	5.2	5.2
Size (Width*Height*Depth mm)	295*230*113	295*230*113	295*230*113	295*230*113	295*230*113	295*230*113
Protection Degree	IP65	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1	<1
Topology	Transformerless					
<b>Certifications &amp; Standards</b>						
Grid Regulation	VDE0126-1-1, EN50438(PL), IEC61727, IEEE1547, G98, ABNT NBR 16149 : 2013					
Safety Regulation	IEC62109-1&-2					
EMC	EN61000					

  Color Options

# DNS Series

Dual MPPT, Single Phase



Technical Data	GW3000D-NS	GW3600D-NS	GW4200D-NS	GW5000D-NS	GW6000D-NS
----------------	------------	------------	------------	------------	------------

## PV String Input Data

Max. DC Input Power (W)	3900	4680	5460	6500	7200
Max. DC Input Voltage (V)	600	600	600	600	600
MPPT Range (V)	80~550	80~550	80~550	80~550	80~550
Start-up Voltage (V)	120	120	120	120	120
MPPT Range for Full Load (V)	150-550	180-550	210-550	250-550	280~550
Nominal DC Input Voltage (V)	360	360	360	360	360
Max. Input Current (A)	11/11	11/11	11/11	11/11	11/11
Max. Short Current (A)	13.8/13.8	13.8/13.8	13.8/13.8	13.8/13.8	13.8/13.8
No. of MPP Trackers	2	2	2	2	2
No. of Input Strings per Tracker	1	1	1	1	1

## AC Output Data

Nominal Output Power (W)	3000*1	3680*1	4200*1	5000*1	6000*1
Max. Output Apparent Power (VA)	3000	3680	4200	5000	6000
Nominal Output Voltage (V)	220/230	220/230	220/230	220/230	220/230
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	13.6	16	19	22.8	27.3
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)				
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%

## Efficiency

Max. Efficiency	97.8%	97.8%	97.8%	97.8%	97.8%
Europe Efficiency	97.5%	97.5%	97.5%	97.5%	97.5%

## Protection

Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated

## General Data

Operating Temperature Range (°C)	-25~60	-25~60	-25~60	-25~60	-25~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Convection				
Noise (dB)	<25	<25	<25	<25	<25
User Interface	LCD & LED	LCD & LED	LCD & LED	LCD & LED	LCD & LED
Communication	RS485 or WiFi	RS485 or WiFi	RS485 or WiFi	RS485 or WiFi	RS485 or WiFi
Weight (kg)	14	14	14	14	14.5
Size (Width*Height*Depth mm)	354*433*147	354*433*147	354*433*147	354*433*147	354*433*147
Protection Degree	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1
Topology	Transformerless				

## Certifications & Standards

Grid Regulation	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G83, IEC61727, IEC62116, CEI 0-21, RD 1699:2011, UNE 206006 IN: 2011, UNE 206007-1 IN: 2013	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G59, IEC61727, MEA, PEA, IEC62116, CEI 0-21, RD 1699:2011, UNE 206006 IN: 2011, UNE 206007-1 IN: 2013	VDE-AR-N 4105, VDE0126-1-1, EN50438(PL), EN50438(SW), AS4777.2, G59, IEC61727, MEA, PEA, IEC62116, CEI 0-21
Safety Regulation	IEC62109-1&-2		
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4, EN61000-4-16, EN61000-4-18, EN61000-4-29		

\*1: For CEI 0-21 Nominal Output Power GW3000D-NS is 2700, GW3680D-NS is 3350, GW4200D-NS is 3800, GW5000D-NS is 4540, GW6000D-NS is 5450.



Color Options

# SDT G2 Series

Dual-MPPT, Three-Phase



Technical Data	GW4K-DT	GW5K-DT	GW6K-DT	GW8K-DT	GW10KT-DT
<b>PV String Input Data</b>					
Max. DC Input Power (Wp)	6000	7500	9000	12000	15000
Max. DC Input Voltage (V)	1000	1000	1000	1000	1000
MPPT Range (V)	180~850	180~850	180~850	180~850	180~850
Start-up Voltage (V)	160	160	160	160	160
MPPT Range for Full Load (V)	180~850	210~850	250~850	330~850	410~850
Max. Input Current (A)	12.5/12.5	12.5/12.5	12.5/12.5	12.5/12.5	12.5/12.5
Max. Short Current (A)	15.6/15.6	15.6/15.6	15.6/15.6	15.6/15.6	15.6/15.6
No. of MPP Trackers	2	2	2	2	2
No. of Input Strings Per MPP Tracker	1/1	1/1	1/1	1/1	1/1
<b>AC Output Data</b>					
Nominal Output Power (W)	4000	5000	6000	8000	10000
Max. Output Apparent Power (VA)	4400	5500	6600	8800	11000
Nominal Output Voltage (V)	400, 3L/N/PE; 3L/PE(Optional)				
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	6.4	8	9.6	12.8	16
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)				
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%
<b>Efficiency</b>					
Max. Efficiency	98.2%	98.2%	98.2%	98.2%	98.3%
Europe Efficiency	97.6%	97.6%	97.6%	97.6%	97.7%
<b>Protection</b>					
Anti-islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated
DC Surge Protection	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)
AC Surge Protection	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)	Integrated(Type III)
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated
Arc Fault Circuit Interrupter	Optional	Optional	Optional	Optional	Optional
Terminal Temperature Detection	Optional	Optional	Optional	Optional	Optional
<b>General Data</b>					
Operating Temperature Range (°C)	-30~60	-30~60	-30~60	-30~60	-30~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Cooling	Natural Cooling	Natural Cooling	Fan Cooling	Fan Cooling
Noise (dB)	<30	<30	<30	<30	<30
User Interface	LCD&LED	LCD&LED	LCD&LED	LCD&LED	LCD&LED
Communication	WiFi or LAN(Optional)	WiFi or LAN(Optional)	WiFi or LAN(Optional)	WiFi or LAN(Optional)	WiFi or LAN(Optional)
Weight (kg)	15	15	15	16	16
Size (Width*Height*Depth mm)	347*432*150	347*432*150	347*432*150	347*432*150	347*432*150
Protection Degree	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1
Topology	Transformerless				
<b>Certifications &amp; Standards</b>					
Grid Regulation	VDE-AR-N 4105, IEC61727, IEC62116				
Safety Regulation	IEC62109-1&-2				
EMC	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4				

# GOODWE GOOD CHOICE

## GoodWe (China)

No.189 Kunlunshan Rd., SND, Suzhou, 215163, China  
T: +86 (0) 512 6239 7998  
sales@goodwe.com  
service.chn@goodwe.com

## GoodWe (Brazil)

Rua Abelardo 45, Recife/PE, 52050-310  
T: +55 54 992504491  
sales@goodwe.com  
servico.br@goodwe.com

## GoodWe (UK)

6 Dunhams Court, Dunhams Lane, Letchworth  
Garden City, SG6 1WB UK  
T: +44 (0) 333 358 3184  
enquiries@goodwe.com.uk  
service@goodwe.com.uk

## GoodWe (Italy)

Via Cesare Braico 61, 72100 Brindisi, Italy  
T: +39 338 879 38 81; +39 831 162 35 52  
valter.pische@goodwe.com  
service.it@goodwe.com

## GoodWe (Australia)

Level 14, 380 St. Kilda Road, Melbourne,  
Victoria, 3004, Australia  
T: +61 (0) 3 9918 3905  
sales@goodwe.com  
service.au@goodwe.com

## GoodWe (Korea)

8F Invest Korea Plaza, 7 Heoleung-ro  
Seocho-gu Seoul Korea (06792)  
T: 82 (2) 3497 1066  
sales@goodwe.com  
Larry.Kim@goodwe.com

## GoodWe (Germany)

Fürstenrieder Str. 279a 81377 München, Germany  
T: +49 8974120210 +49 421 83570-170 (Service)  
sales.de@goodwe.com  
service.de@goodwe.com

## GoodWe (Netherlands)

Franciscusdreef 42C, 3565AC Utrecht, the Netherlands  
T: +31 (0) 30 737 1140  
sales@goodwe.com  
service.nl@goodwe.com

## GoodWe (India)

1202, G-Square Business Park, Sector 30A, Opp. Sanpada  
Railway Stn., Vashi, Navi Mumbai- 400703  
T: +91 (0) 2249746788  
sales@goodwe.com  
service.in@goodwe.com

## GoodWe (Turkey)

Adalet Mah. Megapol Tower K: 9 No: 110 Bayraklı - Izmir  
T: +90 (232) 935 68 18  
info@goodwe.com.tr  
service@goodwe.com.tr

## GoodWe (Mexico)

Oswaldo Sanchez Norte 3615, Col. Hidalgo, Monterrey,  
Nuevo Leon, Mexico, C.P. 64290  
T: +52 1 81 2871 2871  
sales@goodwe.com  
soporte.latam@goodwe.com

Note: The technical data above mentioned may be modified in order to reflect the continuous technical innovation and the improvements achieved by GoodWe's R & D team. GoodWe has the sole right to make such modification at any time without further notice. The GoodWe's customers have the right to request the latest version of the GoodWe products data sheets and all the commercial contracts that may be signed will be based on the most recent version of the data sheet at the moment of signing the contract.

Copyright © GoodWe Power Supply Technology Co., Ltd. 2019. All rights reserved.  
No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of GoodWe Power Supply Technology Co., Ltd.

[www.goodwe.com](http://www.goodwe.com)