

## Motorbike 4T Bike-Additive

### Description

Removes deposits from the fuel system, valves, spark plugs and the combustion chamber while preventing new deposit formation. Improves engine performance and lowers emissions. Provides corrosion protection throughout and prevents carburetor icing.

### Properties

- optimizes engine performance
- prevents corrosion in the fuel system
- reduces residue
- environmentally friendly
- ideal with catalytic converters
- increases operational reliability
- for carburetor and fuel-injection engines
- highly economical
- reduces the risk of knocking combustion
- normalizes fuel consumption and exhaust emissions

### Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °F
Pour point	-49 °F
Form	liquid
Odor	characteristic
Viscosity at 104 °F	<7 mm <sup>2</sup> /s
Density at 59 °F	0,765 g/cm <sup>3</sup>

### Areas of application

Suitable for all 4-stroke gasoline engines. Safe with catalytic converters.

### Comment

**⚠ WARNING: Cancer-** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Application

Contents (125 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

### Available pack sizes

125 ml Can sheet metal 20048  
USA-EN



### Available pack sizes

125 ml Can sheet metal 22096  
CANADA-EN-F

**Our information is based on thorough research and may be considered reliable, although not legally binding.**