## **Product information**

# Brake Anti-Squeal Paste



#### **Description**

A synthetic based specialty with a solid agent to prevent and eliminate noise from brake pads. It is extremely adhesive and high temperature resistant, it resists road salt and water wash-out. With excellent corrosion protection and particularly suited for use with aluminum and magnesium materials as well as on vehicles with ABS/ESP systems.

#### **Properties**

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

#### **Technical data**

Form pastelike, liquid

Color / appearance blue

Base synthetic and ceramic

active ingredients

-40 to +392 short term

as lubricating agent

as release agent

Operating temperature

range to +482 °F

Operating temperature -40 to +2192 °F

range

Odor slight
Shelf life in original 24 months

sealed container

#### Areas of application

Suitable for use in most common disk brake systems. Must never be applied to the friction surface of the brake disc / brake pads.

#### Comment

Do not under any circumstances allow Brake Anti-Squeal Paste to get onto the friction surface of the brake lining or the brake disc.

### **Application**

Clean the surfaces thoroughly before use and then apply to the back of the brake pad and to the contact surfaces and fasteners. Do not apply on friction surfaces!

#### Available pack sizes



#### Available pack sizes

250 g Brush-in-cap can sheet metal 22092

PI 41/10/05/2023

USA-EN

200 ml Can aerosol 20240

**USA-EN** 

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de