Product information

PI 24/03/29/2023

Motorbike Fork Oil 7,5W medium/light



Description

Full synthetic fork oil and shock-absorber oil. Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum driveability and damping. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- good corrosion protection
- prevents seals from swelling
- prevents foam formation
- high wear resistance
- increases driving safety

Technical data

Density at 15 °C 0,825 g/cm³

DIN 51757

Viscosity at 40 °C 22,1 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 4,75 mm²/s

ASTM D 7042-04

Viscosity index 139

DIN ISO 2909

Pour point -54 °C

DIN ISO 3016

Flash point 234 °C

DIN ISO 2592

Color number (ASTM) L 0.5

DIN ISO 2049

Areas of application

Universal use in telescopic forks, shock absorbers in motorcycles, motor bicycles, mopeds and other two-wheeled vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheeled vehicle manufacturers.

Available pack sizes

500 ml Can plastic 3099

D-GB-I-E-P

500 ml Can plastic 5940

D-F-I-GR

1 l Can plastic 2719

D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.



Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de