Product information

Motorbike Speed Shooter



Description

State-of-the-art, ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- good corrosion protection
- residue-free combustion
- guarantees optimum combustion
- improves acceleration
- removes deposits from entire fuel system
- highly economical
- prevents carburetor icing
- higher performance gain

Technical data

Base additive mixture in

carrier fluid

A III

Color / appearance yellow, clear
Odor characteristic

Form liquid
Viscosity at 40 °C <7 mm²/s
Density at 20 °C 0,814 g/cm³

Hazard class as per

German VbF

Flash point >61 °C

Areas of application

For 2-stroke and 4-stroke gasoline engines (aspirated and injection).

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline grades. 80 ml is sufficient for up to 10 liters of fuel.

Available pack sizes

80 ml Can sheet metal 7820

GB

80 ml Can sheet metal 8265

JP

80 ml Can sheet metal 7915

۷N



Available pack sizes

80 ml Can sheet metal 7823

TR

PI 39/08/22/2022

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de